

	1	2	3	4	5	6	7																																																																																															
A	<table><tr><th colspan="2">Properties</th><th>Value</th><th>Unit</th><th>Tolerance</th><th>Test Method</th></tr><tr><td colspan="2">Thermal Conductivity</td><td>7</td><td>W/m·K</td><td>± 0.3</td><td>ASTM D5470</td></tr><tr><td colspan="2">Reinforcement Carrier optional</td><td>Fiberglass mesh</td><td>/</td><td>/</td><td>/</td></tr><tr><td colspan="2">Color*</td><td>Gray white</td><td>/</td><td>/</td><td>Visual</td></tr><tr><td colspan="2">Density</td><td>3.15</td><td>g/cm³</td><td>/</td><td>ASTM D792</td></tr><tr><td colspan="2">Hardness*</td><td>55</td><td>Shore00</td><td>± 5</td><td>ASTM D2240</td></tr><tr><td colspan="2">Tensile strength</td><td>20</td><td>psi</td><td>/</td><td>ASTM D412</td></tr><tr><td colspan="2">Flame Rating</td><td>94V-0</td><td>/</td><td>/</td><td>Equivalent UL</td></tr><tr><td colspan="2">Volume Resistance</td><td>1.3 x 10¹³</td><td>Ω·cm</td><td>/</td><td>ASTM D257</td></tr><tr><td colspan="2">Breakdown Voltage</td><td>≥ 5</td><td>KV/mm</td><td>/</td><td>ASTM D149</td></tr><tr><td colspan="2">Working Temperature</td><td>-40 ~ +150</td><td>°C</td><td>/</td><td>/</td></tr><tr><td colspan="2" rowspan="2">Storage conditions</td><td>Temperature (T)</td><td>15 < T < 30</td><td>°C</td><td>/</td></tr><tr><td>Relative humidity (Rh)</td><td>< 70</td><td>%</td><td>/</td></tr><tr><td colspan="2">Shelf life</td><td>12</td><td>months</td><td>/</td><td>/</td></tr></table> Additional adhesive surface or reinforcement can influence the thermal conductivity. Modification of color or hardness can influence the thermal conductivity. A suitability check is recommended. * other on request Notes: 1. Adhesivity 1.1. Natural tacky 2. Features 2.1. Good thermal conductivity, low thermal resistance 2.2. Good thermal stability 2.3. Good resilience; high reliability for long-term use 2.4. Good insulating material 3. Application options 3.1. Communication equipment, Network terminals, Storage devices, Consumer electronics, power supply devices, security equipment N: Not reinforced / not adhesive / natural tack O: Not reinforced / one side adhesive P: Not reinforced / two sides adhesive ②R: Reinforced(thickness is 1.0mm at least) / not adhesive / natural tack ②S: Reinforced(thickness is 1.0mm at least) / one side adhesive ②T: Reinforced(thickness is 1.0mm at least) / two sides adhesive Order code: VFSGBx-xxxxyyzzz-xy ① Length (x): 005: 5mm (min) 400: 400mm (max) Width (y): 005: 5mm (min) 350: 350mm (max) Thickness (z): 005: 0.5mm (min) 100: 10.0mm (max) <table><tr><th>Properties</th><th>Min (mm)</th><th>Max (mm)</th></tr><tr><td>Length (x)</td><td>5.0</td><td>400.0</td></tr><tr><td>Width (y)</td><td>5.0</td><td>350.0</td></tr><tr><td>Thickness (z)</td><td>0.5</td><td>10.0</td></tr></table> ① Special or other dimensions / sizes on request.							Properties		Value	Unit	Tolerance	Test Method	Thermal Conductivity		7	W/m·K	± 0.3	ASTM D5470	Reinforcement Carrier optional		Fiberglass mesh	/	/	/	Color*		Gray white	/	/	Visual	Density		3.15	g/cm ³	/	ASTM D792	Hardness*		55	Shore00	± 5	ASTM D2240	Tensile strength		20	psi	/	ASTM D412	Flame Rating		94V-0	/	/	Equivalent UL	Volume Resistance		1.3 x 10 ¹³	Ω·cm	/	ASTM D257	Breakdown Voltage		≥ 5	KV/mm	/	ASTM D149	Working Temperature		-40 ~ +150	°C	/	/	Storage conditions		Temperature (T)	15 < T < 30	°C	/	Relative humidity (Rh)	< 70	%	/	Shelf life		12	months	/	/	Properties	Min (mm)	Max (mm)	Length (x)	5.0	400.0	Width (y)	5.0	350.0	Thickness (z)	0.5	10.0	A
Properties								Value	Unit	Tolerance	Test Method																																																																																											
Thermal Conductivity								7	W/m·K	± 0.3	ASTM D5470																																																																																											
Reinforcement Carrier optional								Fiberglass mesh	/	/	/																																																																																											
Color*								Gray white	/	/	Visual																																																																																											
Density								3.15	g/cm ³	/	ASTM D792																																																																																											
Hardness*								55	Shore00	± 5	ASTM D2240																																																																																											
Tensile strength								20	psi	/	ASTM D412																																																																																											
Flame Rating								94V-0	/	/	Equivalent UL																																																																																											
Volume Resistance								1.3 x 10 ¹³	Ω·cm	/	ASTM D257																																																																																											
Breakdown Voltage		≥ 5	KV/mm	/	ASTM D149																																																																																																	
Working Temperature		-40 ~ +150	°C	/	/																																																																																																	
Storage conditions		Temperature (T)	15 < T < 30	°C	/																																																																																																	
		Relative humidity (Rh)	< 70	%	/																																																																																																	
Shelf life		12	months	/	/																																																																																																	
Properties	Min (mm)	Max (mm)																																																																																																				
Length (x)	5.0	400.0																																																																																																				
Width (y)	5.0	350.0																																																																																																				
Thickness (z)	0.5	10.0																																																																																																				
B	B																																																																																																					
C	C																																																																																																					
D	D																																																																																																					
E	E																																																																																																					
F	F																																																																																																					
G	<table><tr><td rowspan="4">RoHS compliant</td><td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td rowspan="2">Description: Thermal foil, containing silicone, Gray white</td></tr><tr><td colspan="2">TOLERANCE</td><td></td><td></td><td></td><td>Drawn</td><td>08.08.2022</td><td>Segal</td></tr><tr><td>0~30</td><td>±0.3</td><td rowspan="2">③</td><td>Add the standard P/N in page 2 to 3</td><td>08.05.2024</td><td>Segal</td><td>Approved</td><td>08.05.2024</td><td>Segal</td><td rowspan="2">ASSMANN WSW-No. VFSGBx-xxxxyyzzz-xy</td></tr><tr><td>31~50</td><td>±0.5</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="4">Unit:mm</td><td>51~400</td><td>±2.0</td><td>②</td><td>Add remark for the order code</td><td>07.12.2023</td><td>Segal</td><td></td><td></td><td></td><td rowspan="4">Drawing-No. ASS 4998 HS rev03</td></tr><tr><td colspan="2">DIM</td><td colspan="2"></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>0~1</td><td>±0.1</td><td>①</td><td>Update</td><td>03.11.2022</td><td>Larsen</td><td colspan="2" rowspan="2"> ASSMANN WSW components A company of BCS </td><td>Customer-No.</td><td rowspan="2">SHEET 1 / 3</td></tr><tr><td>1~10</td><td>±10%</td><td>⑩</td><td>Drawn</td><td>08.08.2022</td><td>Segal</td></tr><tr><td></td><td>T</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td colspan="2"></td><td></td></tr></table>							RoHS compliant	Scale	Free					Date	Name	Description: Thermal foil, containing silicone, Gray white	TOLERANCE					Drawn	08.08.2022	Segal	0~30	±0.3	③	Add the standard P/N in page 2 to 3	08.05.2024	Segal	Approved	08.05.2024	Segal	ASSMANN WSW-No. VFSGBx-xxxxyyzzz-xy	31~50	±0.5						Unit:mm	51~400	±2.0	②	Add remark for the order code	07.12.2023	Segal				Drawing-No. ASS 4998 HS rev03	DIM									0~1	±0.1	①	Update	03.11.2022	Larsen	ASSMANN WSW components A company of BCS		Customer-No.	SHEET 1 / 3	1~10	±10%	⑩	Drawn	08.08.2022	Segal		T	TOL	Id.	Modification	Date	Name				G													
RoHS compliant									Scale	Free					Date	Name		Description: Thermal foil, containing silicone, Gray white																																																																																				
									TOLERANCE					Drawn	08.08.2022	Segal																																																																																						
									0~30	±0.3	③	Add the standard P/N in page 2 to 3	08.05.2024	Segal	Approved	08.05.2024	Segal	ASSMANN WSW-No. VFSGBx-xxxxyyzzz-xy																																																																																				
								31~50	±0.5																																																																																													
Unit:mm	51~400	±2.0	②	Add remark for the order code	07.12.2023	Segal				Drawing-No. ASS 4998 HS rev03																																																																																												
	DIM																																																																																																					
	0~1	±0.1	①	Update	03.11.2022	Larsen	ASSMANN WSW components A company of BCS		Customer-No.		SHEET 1 / 3																																																																																											
	1~10	±10%	⑩	Drawn	08.08.2022	Segal																																																																																																
	T	TOL	Id.	Modification	Date	Name																																																																																																
H	H																																																																																																					
	1	2	3	4	5	6	7																																																																																															

	1	2	3	4	5	6	7																																																																																																																														
A	Standard articles <table><tr><td>③</td><td>Article number</td><td>Length [mm]</td><td>Width [mm]</td><td>Thickness [mm]</td></tr><tr><td></td><td>VFSGBN-015015005-00</td><td>15</td><td>15</td><td>0.5</td></tr><tr><td></td><td>VFSGBN-015015010-00</td><td>15</td><td>15</td><td>1.0</td></tr><tr><td></td><td>VFSGBN-015015015-00</td><td>15</td><td>15</td><td>1.5</td></tr><tr><td></td><td>VFSGBN-015015020-00</td><td>15</td><td>15</td><td>2.0</td></tr><tr><td></td><td>VFSGBN-015015030-00</td><td>15</td><td>15</td><td>3.0</td></tr><tr><td></td><td>VFSGBN-015015040-00</td><td>15</td><td>15</td><td>4.0</td></tr><tr><td></td><td>VFSGBN-030030005-00</td><td>30</td><td>30</td><td>0.5</td></tr><tr><td></td><td>VFSGBN-030030010-00</td><td>30</td><td>30</td><td>1.0</td></tr><tr><td></td><td>VFSGBN-030030015-00</td><td>30</td><td>30</td><td>1.5</td></tr><tr><td></td><td>VFSGBN-030030020-00</td><td>30</td><td>30</td><td>2.0</td></tr><tr><td></td><td>VFSGBN-030030030-00</td><td>30</td><td>30</td><td>3.0</td></tr><tr><td></td><td>VFSGBN-030030040-00</td><td>30</td><td>30</td><td>4.0</td></tr><tr><td></td><td>VFSGBN-050050005-00</td><td>50</td><td>50</td><td>0.5</td></tr><tr><td></td><td>VFSGBN-050050010-00</td><td>50</td><td>50</td><td>1.0</td></tr><tr><td></td><td>VFSGBN-050050015-00</td><td>50</td><td>50</td><td>1.5</td></tr><tr><td></td><td>VFSGBN-050050020-00</td><td>50</td><td>50</td><td>2.0</td></tr><tr><td></td><td>VFSGBN-050050030-00</td><td>50</td><td>50</td><td>3.0</td></tr><tr><td></td><td>VFSGBN-050050040-00</td><td>50</td><td>50</td><td>4.0</td></tr><tr><td></td><td>VFSGBN-100100005-00</td><td>100</td><td>100</td><td>0.5</td></tr><tr><td></td><td>VFSGBN-100100010-00</td><td>100</td><td>100</td><td>1.0</td></tr><tr><td></td><td>VFSGBN-100100015-00</td><td>100</td><td>100</td><td>1.5</td></tr><tr><td></td><td>VFSGBN-100100020-00</td><td>100</td><td>100</td><td>2.0</td></tr><tr><td></td><td>VFSGBN-100100030-00</td><td>100</td><td>100</td><td>3.0</td></tr><tr><td></td><td>VFSGBN-100100040-00</td><td>100</td><td>100</td><td>4.0</td></tr></table>							③	Article number	Length [mm]	Width [mm]	Thickness [mm]		VFSGBN-015015005-00	15	15	0.5		VFSGBN-015015010-00	15	15	1.0		VFSGBN-015015015-00	15	15	1.5		VFSGBN-015015020-00	15	15	2.0		VFSGBN-015015030-00	15	15	3.0		VFSGBN-015015040-00	15	15	4.0		VFSGBN-030030005-00	30	30	0.5		VFSGBN-030030010-00	30	30	1.0		VFSGBN-030030015-00	30	30	1.5		VFSGBN-030030020-00	30	30	2.0		VFSGBN-030030030-00	30	30	3.0		VFSGBN-030030040-00	30	30	4.0		VFSGBN-050050005-00	50	50	0.5		VFSGBN-050050010-00	50	50	1.0		VFSGBN-050050015-00	50	50	1.5		VFSGBN-050050020-00	50	50	2.0		VFSGBN-050050030-00	50	50	3.0		VFSGBN-050050040-00	50	50	4.0		VFSGBN-100100005-00	100	100	0.5		VFSGBN-100100010-00	100	100	1.0		VFSGBN-100100015-00	100	100	1.5		VFSGBN-100100020-00	100	100	2.0		VFSGBN-100100030-00	100	100	3.0		VFSGBN-100100040-00	100	100	4.0	A
③								Article number	Length [mm]	Width [mm]	Thickness [mm]																																																																																																																										
								VFSGBN-015015005-00	15	15	0.5																																																																																																																										
								VFSGBN-015015010-00	15	15	1.0																																																																																																																										
								VFSGBN-015015015-00	15	15	1.5																																																																																																																										
								VFSGBN-015015020-00	15	15	2.0																																																																																																																										
								VFSGBN-015015030-00	15	15	3.0																																																																																																																										
								VFSGBN-015015040-00	15	15	4.0																																																																																																																										
								VFSGBN-030030005-00	30	30	0.5																																																																																																																										
								VFSGBN-030030010-00	30	30	1.0																																																																																																																										
								VFSGBN-030030015-00	30	30	1.5																																																																																																																										
								VFSGBN-030030020-00	30	30	2.0																																																																																																																										
								VFSGBN-030030030-00	30	30	3.0																																																																																																																										
								VFSGBN-030030040-00	30	30	4.0																																																																																																																										
								VFSGBN-050050005-00	50	50	0.5																																																																																																																										
								VFSGBN-050050010-00	50	50	1.0																																																																																																																										
								VFSGBN-050050015-00	50	50	1.5																																																																																																																										
								VFSGBN-050050020-00	50	50	2.0																																																																																																																										
								VFSGBN-050050030-00	50	50	3.0																																																																																																																										
								VFSGBN-050050040-00	50	50	4.0																																																																																																																										
	VFSGBN-100100005-00	100	100	0.5																																																																																																																																	
	VFSGBN-100100010-00	100	100	1.0																																																																																																																																	
	VFSGBN-100100015-00	100	100	1.5																																																																																																																																	
	VFSGBN-100100020-00	100	100	2.0																																																																																																																																	
	VFSGBN-100100030-00	100	100	3.0																																																																																																																																	
	VFSGBN-100100040-00	100	100	4.0																																																																																																																																	
B								B																																																																																																																													
C								C																																																																																																																													
D								D																																																																																																																													
E								E																																																																																																																													
F								F																																																																																																																													
G	RoHS compliant Unit:mm		Scale	Free					Date	Name	Description: Thermal foil, containing silicone, Gray white	G																																																																																																																									
TOLERANCE							Drawn	08.08.2022	Segal																																																																																																																												
0~30			±0.3	③	Add the standard P/N in page 2 to 3	08.05.2024	Segal	Approved	08.05.2024	Segal	ASSMANN WSW-No. VFSGBx-xxxxyyzzz-xy	H																																																																																																																									
31~50			±0.5																																																																																																																																		
51~400			±2.0	②	Add remark for the order code	07.12.2023	Segal																																																																																																																														
DIM			TOL	①	Update	03.11.2022	Larsen	ASSMANN WSW components A company of BCS		Drawing-No. ASS 4998 HS		rev03																																																																																																																									
0~1			±0.1		⑩	Drawn	08.08.2022			Segal	Customer-No.		SHEET 2 / 3																																																																																																																								
1~10			±10%																																																																																																																																		
H	T	TOL	Id.	Modification	Date	Name																																																																																																																															
	1	2	3	4	5	6	7																																																																																																																														

	1	2	3	4	5	6	7																													
A	Standard articles ③<table><tr><th>Article number</th><th>Length [mm]</th><th>Width [mm]</th><th>Thickness [mm]</th></tr><tr><td>VFSGBN-150150005-00</td><td>150</td><td>150</td><td>0.5</td></tr><tr><td>VFSGBN-150150010-00</td><td>150</td><td>150</td><td>1.0</td></tr><tr><td>VFSGBN-150150015-00</td><td>150</td><td>150</td><td>1.5</td></tr><tr><td>VFSGBN-150150020-00</td><td>150</td><td>150</td><td>2.0</td></tr><tr><td>VFSGBN-150150030-00</td><td>150</td><td>150</td><td>3.0</td></tr><tr><td>VFSGBN-150150040-00</td><td>150</td><td>150</td><td>4.0</td></tr></table>							Article number	Length [mm]	Width [mm]	Thickness [mm]	VFSGBN-150150005-00	150	150	0.5	VFSGBN-150150010-00	150	150	1.0	VFSGBN-150150015-00	150	150	1.5	VFSGBN-150150020-00	150	150	2.0	VFSGBN-150150030-00	150	150	3.0	VFSGBN-150150040-00	150	150	4.0	A
Article number								Length [mm]	Width [mm]	Thickness [mm]																										
VFSGBN-150150005-00								150	150	0.5																										
VFSGBN-150150010-00								150	150	1.0																										
VFSGBN-150150015-00								150	150	1.5																										
VFSGBN-150150020-00								150	150	2.0																										
VFSGBN-150150030-00								150	150	3.0																										
VFSGBN-150150040-00	150	150	4.0																																	
B	B																																			
C	C																																			
D	D																																			
E	E																																			
F	F																																			
G	RoHS compliant Unit:mm		Scale	Free					Date	Name	Description: Thermal foil, containing silicone, Gray white	G																								
TOLERANCE							Drawn	08.08.2022	Segal																											
0~30			±0.3																																	
31~50			±0.5	③	Add the standard P/N in page 2 to 3	08.05.2024	Segal	Approved	08.05.2024	Segal	ASSMANN WSW-No. VFSGBx-xxxxyyyzzz-xy		H																							
51~400			±2.0	②	Add remark for the order code	07.12.2023	Segal																													
DIM			TOL	①	Update	03.11.2022	Larsen	ASSMANN WSW components A company of BCS			Drawing-No. ASS 4998 HS	rev03																								
0~1			±0.1																																	
1~10			±10%	④	Drawn	08.08.2022	Segal				Customer-No.	SHEET 3 / 3																								
	T	TOL	Id.	Modification	Date	Name																														
	1	2	3	4	5	6	7																													