



1		2		3		4		5		6		7																																																																																																	
A	<table><thead><tr><th colspan="2">Properties</th><th>Value</th><th>Unit</th><th>Tolerance</th><th>Test Method</th></tr></thead><tbody><tr><td colspan="2">Thermal Conductivity</td><td>12</td><td>W/m·K</td><td>± 0.3</td><td>ASTM D5470</td></tr><tr><td colspan="2">Reinforcement Carrier optional</td><td>Fiberglass mesh</td><td>/</td><td>/</td><td>/</td></tr><tr><td colspan="2">Color*</td><td>Dark Gray</td><td>/</td><td>/</td><td>Visual</td></tr><tr><td colspan="2">Density</td><td>3.28</td><td>g/cm³</td><td>/</td><td>ASTM D792</td></tr><tr><td colspan="2">Hardness*</td><td>65</td><td>Shore00</td><td>± 5</td><td>ASTM D2240</td></tr><tr><td colspan="2">Tensile strength</td><td>20</td><td>psi</td><td>/</td><td>ASTM D412</td></tr><tr><td colspan="2">Flame Rating</td><td>94V-0</td><td>/</td><td>/</td><td>Equivalent UL</td></tr><tr><td colspan="2">Volume Resistance</td><td>1.1x 10¹³</td><td>Ω·cm</td><td>/</td><td>ASTM D257</td></tr><tr><td colspan="2">Breakdown Voltage</td><td>≥ 5</td><td>KV/mm</td><td>/</td><td>ASTM D149</td></tr></tbody></table>												Properties		Value	Unit	Tolerance	Test Method	Thermal Conductivity		12	W/m·K	± 0.3	ASTM D5470	Reinforcement Carrier optional		Fiberglass mesh	/	/	/	Color*		Dark Gray	/	/	Visual	Density		3.28	g/cm ³	/	ASTM D792	Hardness*		65	Shore00	± 5	ASTM D2240	Tensile strength		20	psi	/	ASTM D412	Flame Rating		94V-0	/	/	Equivalent UL	Volume Resistance		1.1x 10 ¹³	Ω·cm	/	ASTM D257	Breakdown Voltage		≥ 5	KV/mm	/	ASTM D149	Notes: 1. Adhesivity 1.1. Natural tacky 2. Features 2.1. Good thermal conductivity, low thermal resistance 2.2. Good thermal stability 2.3. Good resilience; high reliability for long-term use 2.4. Good insulating material 3. Application options 3.1. Communication equipment, Network terminals, Storage devices, Consumer electronics, power supply devices, security equipment	A																																			
	Properties		Value	Unit	Tolerance	Test Method																																																																																																							
	Thermal Conductivity		12	W/m·K	± 0.3	ASTM D5470																																																																																																							
	Reinforcement Carrier optional		Fiberglass mesh	/	/	/																																																																																																							
	Color*		Dark Gray	/	/	Visual																																																																																																							
	Density		3.28	g/cm ³	/	ASTM D792																																																																																																							
	Hardness*		65	Shore00	± 5	ASTM D2240																																																																																																							
	Tensile strength		20	psi	/	ASTM D412																																																																																																							
	Flame Rating		94V-0	/	/	Equivalent UL																																																																																																							
	Volume Resistance		1.1x 10 ¹³	Ω·cm	/	ASTM D257																																																																																																							
Breakdown Voltage		≥ 5	KV/mm	/	ASTM D149																																																																																																								
B	<table><tbody><tr><td rowspan="2">Storage conditions</td><td>Temperature (T)</td><td>15 < T < 30</td><td>°C</td><td>/</td><td>/</td></tr><tr><td>Relative humidity (Rh)</td><td>< 70</td><td>%</td><td>/</td><td>/</td></tr><tr><td colspan="2">Shelf life</td><td>12</td><td>months</td><td>/</td><td>/</td></tr></tbody></table>												Storage conditions	Temperature (T)	15 < T < 30	°C	/	/	Relative humidity (Rh)	< 70	%	/	/	Shelf life		12	months	/	/	B																																																																															
	Storage conditions	Temperature (T)	15 < T < 30	°C	/	/																																																																																																							
		Relative humidity (Rh)	< 70	%	/	/																																																																																																							
	Shelf life		12	months	/	/																																																																																																							
	C	Additional adhesive surface or reinforcement can influence the thermal conductivity. Modification of color or hardness can influence the thermal conductivity. A suitability check is recommended. * other on request												C																																																																																															
		D	Thermal Resistance V.S Pressure  <table><thead><tr><th></th><th>10Psi</th><th>20Psi</th><th>30Psi</th><th>40Psi</th><th>50Psi</th></tr></thead><tbody><tr><td>R(°C*in²/W)</td><td>0.248</td><td>0.110</td><td>0.062</td><td>0.050</td><td>0.048</td></tr></tbody></table>  <table><thead><tr><th>Properties</th><th>Min (mm)</th><th>Max (mm)</th></tr></thead><tbody><tr><td>Length (x)</td><td>5.0</td><td>400.0</td></tr><tr><td>Width (y)</td><td>5.0</td><td>350.0</td></tr><tr><td>Thickness (z)</td><td>0.8</td><td>10.0</td></tr></tbody></table> ① Special or other dimensions / sizes on request.													10Psi	20Psi	30Psi	40Psi	50Psi	R(°C*in²/W)	0.248	0.110	0.062	0.050	0.048	Properties	Min (mm)	Max (mm)		Length (x)	5.0	400.0	Width (y)	5.0	350.0	Thickness (z)	0.8	10.0	D																																																																					
				10Psi	20Psi	30Psi	40Psi	50Psi																																																																																																					
			R(°C*in²/W)	0.248	0.110	0.062	0.050	0.048																																																																																																					
			Properties	Min (mm)	Max (mm)																																																																																																								
			Length (x)	5.0	400.0																																																																																																								
Width (y)			5.0	350.0																																																																																																									
Thickness (z)			0.8	10.0																																																																																																									
E			Order code: VFSLAx-xxxxxyyyzzz-xy ① Length (x): 005: 5mm (min) 400: 400mm (max) Width (y): 005: 5mm (min) 350: 350mm (max) Thickness (z): 008: 0.8mm (min) 100: 10.0mm (max) 0: Width y.0mm 5: Width y.5mm 0: Length x.0mm 5: Length x.5mm												E																																																																																														
			F													F																																																																																													
	G			<table><thead><tr><th>Scale</th><th>Free</th><th></th><th></th><th></th><th></th><th></th><th>Date</th><th>Name</th><th>Description:</th></tr></thead><tbody><tr><td colspan="2">TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td>Drawn</td><td>08.08.2022</td><td>Segal</td><td>Thermal foil, containing silicone, Dark Gray</td></tr><tr><td>0~30</td><td>±0.3</td><td></td><td></td><td></td><td></td><td></td><td>Approved</td><td>09.05.2024</td><td>Segal</td><td>ASSMANN WSW-No.</td></tr><tr><td>31~50</td><td>±0.5</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td rowspan="4">VFSLAx-xxxxxyyyzzz-xy</td></tr><tr><td>51~400</td><td>±2.0</td><td>②</td><td>Add the standard P/N in page 2</td><td>09.05.2024</td><td>Segal</td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td>①</td><td>Update</td><td>03.11.2022</td><td>Larsen</td><td colspan="3" rowspan="2"> A company of BCS</td><td>Drawing-No.</td><td>ASS 5002 HS</td><td>rev02</td></tr><tr><td>0~1</td><td>±0.1</td><td></td><td></td><td></td><td></td><td>Customer-No.</td><td>SHEET 1 / 2</td></tr><tr><td>1~10</td><td>±10%</td><td>③</td><td>Drawn</td><td>08.08.2022</td><td>Segal</td><td></td><td></td><td></td></tr><tr><td>T</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>													Scale	Free						Date	Name	Description:	TOLERANCE							Drawn	08.08.2022	Segal	Thermal foil, containing silicone, Dark Gray	0~30	±0.3							Approved	09.05.2024	Segal	ASSMANN WSW-No.	31~50	±0.5									VFSLAx-xxxxxyyyzzz-xy	51~400	±2.0	②	Add the standard P/N in page 2	09.05.2024	Segal				DIM	TOL	①	Update	03.11.2022	Larsen	 A company of BCS			Drawing-No.	ASS 5002 HS	rev02	0~1	±0.1					Customer-No.	SHEET 1 / 2	1~10	±10%	③	Drawn	08.08.2022	Segal				T	TOL	Id.	Modification	Date	Name					
		Scale		Free						Date	Name	Description:																																																																																																	
		TOLERANCE							Drawn	08.08.2022	Segal	Thermal foil, containing silicone, Dark Gray																																																																																																	
		0~30		±0.3						Approved	09.05.2024	Segal	ASSMANN WSW-No.																																																																																																
		31~50		±0.5									VFSLAx-xxxxxyyyzzz-xy																																																																																																
		51~400		±2.0	②	Add the standard P/N in page 2	09.05.2024	Segal																																																																																																					
		DIM		TOL	①	Update	03.11.2022	Larsen	 A company of BCS			Drawing-No.		ASS 5002 HS			rev02																																																																																												
		0~1		±0.1								Customer-No.		SHEET 1 / 2																																																																																															
1~10		±10%		③	Drawn	08.08.2022	Segal																																																																																																						
T		TOL	Id.	Modification	Date	Name																																																																																																							
H	RoHS compliant Unit:mm												H																																																																																																

	1	2	3	4	5	6	7																																																									
A	Standard articles ②<table><tr><th>Article number</th><th>Length [mm]</th><th>Width [mm]</th><th>Thickness [mm]</th></tr><tr><td>VFSLAN-015015010-00</td><td>15</td><td>15</td><td>1.0</td></tr><tr><td>VFSLAN-015015015-00</td><td>15</td><td>15</td><td>1.5</td></tr><tr><td>VFSLAN-015015020-00</td><td>15</td><td>15</td><td>2.0</td></tr><tr><td>VFSLAN-015015030-00</td><td>15</td><td>15</td><td>3.0</td></tr><tr><td>VFSLAN-015015040-00</td><td>15</td><td>15</td><td>4.0</td></tr><tr><td>VFSLAN-030030010-00</td><td>30</td><td>30</td><td>1.0</td></tr><tr><td>VFSLAN-030030015-00</td><td>30</td><td>30</td><td>1.5</td></tr><tr><td>VFSLAN-030030020-00</td><td>30</td><td>30</td><td>2.0</td></tr><tr><td>VFSLAN-030030030-00</td><td>30</td><td>30</td><td>3.0</td></tr><tr><td>VFSLAN-030030040-00</td><td>30</td><td>30</td><td>4.0</td></tr><tr><td>VFSLAN-050050010-00</td><td>50</td><td>50</td><td>1.0</td></tr><tr><td>VFSLAN-050050015-00</td><td>50</td><td>50</td><td>1.5</td></tr><tr><td>VFSLAN-100100010-00</td><td>100</td><td>100</td><td>1.0</td></tr></table>							Article number	Length [mm]	Width [mm]	Thickness [mm]	VFSLAN-015015010-00	15	15	1.0	VFSLAN-015015015-00	15	15	1.5	VFSLAN-015015020-00	15	15	2.0	VFSLAN-015015030-00	15	15	3.0	VFSLAN-015015040-00	15	15	4.0	VFSLAN-030030010-00	30	30	1.0	VFSLAN-030030015-00	30	30	1.5	VFSLAN-030030020-00	30	30	2.0	VFSLAN-030030030-00	30	30	3.0	VFSLAN-030030040-00	30	30	4.0	VFSLAN-050050010-00	50	50	1.0	VFSLAN-050050015-00	50	50	1.5	VFSLAN-100100010-00	100	100	1.0	A
Article number								Length [mm]	Width [mm]	Thickness [mm]																																																						
VFSLAN-015015010-00								15	15	1.0																																																						
VFSLAN-015015015-00								15	15	1.5																																																						
VFSLAN-015015020-00								15	15	2.0																																																						
VFSLAN-015015030-00								15	15	3.0																																																						
VFSLAN-015015040-00								15	15	4.0																																																						
VFSLAN-030030010-00								30	30	1.0																																																						
VFSLAN-030030015-00								30	30	1.5																																																						
VFSLAN-030030020-00								30	30	2.0																																																						
VFSLAN-030030030-00								30	30	3.0																																																						
VFSLAN-030030040-00								30	30	4.0																																																						
VFSLAN-050050010-00								50	50	1.0																																																						
VFSLAN-050050015-00								50	50	1.5																																																						
VFSLAN-100100010-00								100	100	1.0																																																						
B								B																																																								
C	C																																																															
D	D																																																															
E	E																																																															
F	F																																																															
G	RoHS compliant Unit:mm	Scale	Free				Date	Name	Description: Thermal foil, containing silicone, Dark Gray	G																																																						
		TOLERANCE					Drawn	08.08.2022	Segal																																																							
		0~30	±0.3				Approved	09.05.2024	Segal	ASSMANN WSW-No. VFSLAx-xxxxyyyzzz-xy																																																						
		31~50	±0.5																																																													
		51~400	±2.0	②	Add the standard P/N in page 2	09.05.2024	Segal																																																									
		DIM	TOL	①	Update	03.11.2022	Larsen	ASSMANN WSW components A company of BCS		Drawing-No. ASS 5002 HS	rev02																																																					
		0~1	±0.1																																																													
		1~10	±10%	③	Drawn	08.08.2022	Segal																																																									
H		T	TOL	Id.	Modification	Date	Name	Customer-No.	SHEET 2 / 2	H																																																						
	1	2	3	4	5	6	7																																																									