

WBISK 3

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Similar to illustration











If you demand effective and exact work, it is essential to use the precise torque. This also guarantees high repetition accuracy.

This is the perfect job for the new Weidmüller torque screwdriver with the ergonomic grip and the unique interchangeable bit system.

- Compact and especially light design
- Torque set with special tool (supplied); an unintended, incorrect setting is ruled out.
- Ergonomic handle sizes matched to the torque range.
- Tools subjected to routine testing and provided with an ID number; 100% quality control with verification and product reference.
- Clicking sound upon reaching the set torque, clearly audible and noticeable, no unnecessary tightening.
- Interchangeable blades made from high-quality wearresistant tool steel.
- All tools fulfil the accuracy requirements of: EN ISO 6798, BS EN 26789, ASME B107.14M
- Trigger accuracy +/- 6% of the set scale value.

General ordering data

| Version | Screwdriver insert | |
|------------|--------------------|---|
| Order No. | <u>2506060000</u> | |
| Туре | WBISK 3 | |
| GTIN (EAN) | 4050118520552 | - |
| Qty. | 1 pc(s). | |
| Packaging | miscellaneous | |



WBISK3

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Technical data

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

Dimensions and weights

| Depth | 7 mm | Depth (inches) | www.weidmue lle2.76ni nch |
|------------|-------|-----------------|----------------------------------|
| Height | 75 mm | Height (inches) | 2.953 inch |
| Width | 7 mm | Width (inches) | 0.276 inch |
| Net weight | 8.9 g | | |

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical data

Description of article VDE insulated

interchangeable blade for hexagonal head screws

Screwing tools

| Form | Hexagon / Allen key | Size | 3 | |
|--------------------|---------------------|---------------|---|--|
| Torque setting max | 5.5 Nm | - | | |

Classifications

| ETIM 6.0 | EC002120 | ETIM 7.0 | EC002120 |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC002120 | ECLASS 9.0 | 21-04-92-19 |
| ECLASS 9.1 | 21-04-04-90 | ECLASS 10.0 | 21-04-92-19 |
| ECLASS 11.0 | 21-04-04-35 | ECLASS 12.0 | 21-04-04-35 |

Downloads

| Approval/Certificate/Document of | |
|----------------------------------|--|
| Conformity | Manufacturer's Declaration - Slim Bits |
| Catalogues | Catalogues in PDF-format |