

## Product data sheet

# 636 084 3

## Crimping machine CM 25-3

With ferrule crimping unit

- Compact, maintenance-free tabletop machine in several variants
- Hand or foot actuation
- Height-adjustable feet
- Quick and simple retooling makes it suitable for short- and medium-run production
- Crimp unit for insulated and uninsulated 0.08 mm<sup>2</sup> to 10 mm<sup>2</sup> ferrules
- Square crimp profile with 4 profiled crimp surfaces
- Self-adjusting adaptation to the required size of wire-end ferrule
- Adjustable insertion guide for insulated wire-end ferrules



### General

|             |                    |
|-------------|--------------------|
| Item number | 636 084 3          |
| EAN         | 4049002097348      |
| Weight      | 32,400 g           |
| Dimension   | 325 x 280 x 500 mm |

### Specifications

|                                    |                             |
|------------------------------------|-----------------------------|
| Crimp force                        | 25 kN                       |
| Operating pressure                 | 6 bar                       |
| Air requirement per working stroke | 0.75 l                      |
| Range of applications              | Ferrules                    |
| Capacity                           | 0.08 – 10.0 mm <sup>2</sup> |

### Contents

|             |                                                                  |
|-------------|------------------------------------------------------------------|
| 636 084 3 0 | Ferrule Crimping Unit, Square Crimp, 0.08 — 10.0 mm <sup>2</sup> |
|-------------|------------------------------------------------------------------|

*With reservations regarding technical modifications and errors. Illustration may vary.*