Elpress mini

- electro-hydraulic crimping tool 6 to 70 mm²



The Elpress mini tool PVL350 in a new sleek design with a high performance Li-Ion battery that streamlines your work with its improved battery capacity.

CHARACTERISTICS:

- Single-handed operation for easy control of all tool functions
- Slim fitting crimping head ideal for confined spaces
- High-performance 12 V Li-lon battery with indication of charge status
- Opening, rotatable "flip-top" head for easy die change and good accessibility
- Easy and comfortable to use with one hand thanks to its ergonomic 2-component housing with grip-friendly protection
- Extremely lightweight and rapid crimping process for maximum efficiency
- Automatic return of dies when crimping is completed

TECHNICAL DATA PVL350:

Crimping force 35 kN **Crimping range** 6-70 mm²

Crimping process about 3-4 s (dependent on material)

Number of crimps about 180 for 70 mm² Cu

Battery voltage 12 V

Battery capacity 1.5 Ah, Li-lon
Charge time about 40 minutes.

Weight including battery 1.6 kg


Ambient temperature -10°C to +40°C

Dimensions 330 x 85 x 60 mm

Elpress MINI - crimping dies



Application		Area	Dies	
CUT-connector		6-16 mm²	MB4016	
		KR/KRD, KS/KSD	KR/KRF, KS/KSF	KRT/KST
Hexagonal 4-10 mm ²		MB4016	MB4016	-
Hexagonal 10 mm ²		MB8	MB8	MB7
\$	16 mm²	MB8	MB9	MB8,5
	25 mm ²	MB9	MB11	MB10
	35 mm²	MB11	MB13	MB12
	50 mm ²	MB12	MB14,5	MB14
	70 mm²	MB14	MB17	MB16
	95 mm²	MB17		
C-connectors		12-26 mm² (C6-10)	MBC5	
		30-50 mm² (C16-25)	MBC6	



E-mail: sales@elpress.us | www.elpress.us

