



## 1-Channel Power Unit, 200 W

Item No: WX1N

1-Channel Power Unit, 200 W

### KEY FEATURES

- + Robust touch screen with ESD safe glass
- + Intuitive use with turn-click-wheel with enter key and finger guide
- + Blue LED backlighting
- + Multilingual menu navigation
- + High functionality
- + No safety rest with Stop & Go function needed thanks to integrated acceleration sensor
- + Optimized precision, better stability by sensor in the soldering iron

## TECHNICAL DATA

Dimensions L x W x H	174.0 x 154.0 x 135.0mm
Automatic Tool Identification	Yes
Benchtop Controller	Yes
Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3.5mm Pawl Socket on Back of Device
ESD Safe	Yes
Fuse	T2A
Interface	1x USB, 2x RS232, 1x Switching Output
Multilingual Display	Yes
Number of Channels	1
Power	200 W
Temperature Accuracy °C	± 9 °C
Temperature Accuracy °F	±17 °C
Temperature Range (Depends on Tool)	199 - 998°F
Temperature Range °C	100 - 450 °C
Temperature Range °F	200 - 850 °F
Temperature Stability °C	±2 °C
Temperature Stability °F	±4 °F
Tip Type	WX
Traceability	Yes
UPC	037103304766
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Voltage	120 V
Weight (Catalog)	3.42 kg