


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00313	Connector, dc plug, 5.5x2.1xL21mm, brass, nickel-plated, molding type, white insulators	1	
2	30-00405	Wire, 2C TS, 24 AWG, UL2468, 300V, 80C, 3.0 mm, VW-1, PVC, 87A, white	1	
3	24-00003	Overmold, PVC, white	1	




Notes:

Cables individually tied and bundled in groups of 10

Functionally equivalent components may be substituted

4.5 A, 48 Vdc

Wiring Diagram	
50-00313	wire color
center	white with stripe
sleeve	white

Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	12/11/2015	Initial release	Verified:		
			Dimensions are in millimeters.	Description:	Size: A Part number: 10-01241
			Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm		
				Cable, 1830 mm, 5.5x2.1x12 mm 50-00313 dc plug to stripped tinned, 24 AWG, 30-00405 wire, white	Scale: 1:1  Sheet 1 of 1