


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00313	Connector, dc plug, 5.5x2.1xL21mm, brass, nickel-plated, molding type, white insulators	1	
2	50-00025	Connector, dc jack, 5.5x2.1xL17.4 mm, molding style	1	
3	30-00396	Wire, 2C TS, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, white	1	
4	24-00003	Overmold, PVC, white	1	
5	24-00004	Overmold, PVC, white	1	



Notes:

Cables individually tied and bundled in groups of 10

Functionally equivalent components may be substituted

7 A, 48 Vdc

Wiring Diagram		
50-00313	wire color	50-00025
center	white with stripe	center
sleeve	white	sleeve

Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	10/31/2014	Initial release	Verified:	RoHS compliant	
				Function test: no open, no short circuit, no intermittent	
			Dimensions are in millimeters.	Description:	
			Tolerances:	Cable, 1830 mm, 5.5x2.1x12mm 50-00313 plug to 5.5x2.1mm 50-00025 jack, 18 AWG, 30-00396 wire, white	
			X: ± 0.5 mm		Size: A
			X.X: ± 0.3 mm		Part number: 10-01248
			X.XX: ± 0.05 mm		Scale: 1:2
					Sheet 1 of 1