
ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	54-00187	Connector, 3 pin M12 A-code plug, 12xL24mm, gold plated, panel mount, solder cup, IP67	1	nut and o-ring included
2	Wire	Wire, hook-up, TS, 24 AWG, UL 11028, 600V, 105C, 1.1 mm, mPPE	3	color: red, black, white
3	Heat shrink	Heat shrink, UL, black	3	covers solder joints



Cable rated for 250 V, 4 A
Temperature: -40 ~ 105 °C

IP67 waterproof rating when mated with corresponding (IP67) connector and installed properly in panel

Cables individually packaged in PE bag Functionally equivalent components may be substituted

5

01					
Frank Vianu					
Front View					
Not to Scale					

Wiring Diagram						
54-00187 wire color (P/N						
1	red (30-01762)					
3	black (30-01763)					
4	white (30-01764)					

Revision:	Date:	Description:	Prepared:	Notes:					
Α	4/19/2021	Initial release		RoHS compliant	TENSILITY		LITY		
			Verified:			. —			
				Function test: no open, no short circuit, no			877.670.7118		
				intermittent	fax	x 1.541.323.4202 we	b tensility.com		
			Dimensions are in						
			 millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm 	Tolerances:	Description:	Size:	Part number:		
					+ 0.5 mm Cable, 305 mm, M12 3C plug panel mount 54-00187	Α	10-04031		
				to blunt cut, 24 AWG, UL 11028 hook-up wire	Scale:	1:1	Sheet 1 of 1		

3 2