

1	2	3	4	5	6	7	8	
				REV. B	ECN NO. LEN-750207	DATE 2007/05/11	SIGN Jason	DESCRIPTION Change Position Of Polarization.
				C	LEN-930611~614	2009/02/04	ZhaoRongFu	Update the drawing.
				D	LEN1660495~498	2016/06/06	Vicky	Update Logo

12P-05BFIM-SL8000
Color:Black

12P-05BFIM-SL8AXX

XX:01~99Meters
01:01Meter
02:02Meters
:
:
99:99Meters

Cable Length(L):01~99Meters

ALTW
CONFIDENTIAL
2016.06.06
R&D DEPT.

ALTW
DCC. DEPT.
CONFIDENTIAL
2016.06.08
ISSUED

Pin Assignments
Front View

5	Green	綠
4	Black	黑
3	Blue	藍
2	White	白
1	Brown	棕
Conn.	Wire Color	

Pin Out

UNIT:mm

TOLERANCE ±0.5 mm

TITLE M12 Conn
Cable Screw 5P F Conn I Pin

SCALE Free

REV. D

SHEET 1 OF 1

SIZE A4

QC :Inspection Item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO

DWG NO 12P-05BFIM-SL8AXX

CUSTOMER ALTW

DRAWN BY Vicky

CHECKED BY Rita

APPROVED BY Lisa

DATE 2016/06/06

DATE 2016/06/06

DATE 2016/06/06

Note:

- * @C Important Dimension.
- * Waterproof Rate:IP68.
In 1 meter water within 24 hours.
- * Connector:PU,Black.
- * Pin:Copper Alloy,Gold Plated.
- * Cable:UL2464 22AWG*5C+Talcum,Black,
PVC Jacket,UV Resistant,OD=5.5mm.
- * Cable Length Tolerance: 01M:±40mm
02M~05M:±60mm
06M~10M:±100mm
11M~30M:±200mm
31M~99M:±500mm

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.