



8-pin Single-Ended M12 Female Shielded Cordsets





Features

- M12 female to flying leads, eight conductors, multiple length options
- Black PVC jacket, foil shield with unterminated 24 AWG drain, A-code connector
- Straight and right-angle connector options

Models

8-pin Single-Ended M12 Female Shielded Cordsets				
Model	Length	Dimensions (mm)	Pinout (Female)	
BC-M12F8-24-1-SF	1 m (3.28 ft)			<ul style="list-style-type: none">1 = White2 = Brown3 = Green4 = Yellow5 = Gray6 = Pink7 = Blue8 = Red
BC-M12F8-24-2-SF	2 m (6.56 ft)			
BC-M12F8-24-5-SF	5 m (16.4 ft)			
BC-M12F8-24-8-SF	8 m (26.25 ft)			
BC-M12F8-24-10-SF	10 m (30.81 ft)			
BC-M12F8-24-15-SF	15 m (49.2 ft)			

8-pin Single-Ended M12 Female Right-Angle Shielded Cordsets				
Model	Length	Dimensions (mm)	Pinout (Female)	
BC-M12F8A-24-1-SF	1 m (3.28 ft)			<ul style="list-style-type: none">1 = White2 = Brown3 = Green4 = Yellow5 = Gray6 = Pink7 = Blue8 = Red
BC-M12F8A-24-2-SF	2 m (6.56 ft)			
BC-M12F8A-24-5-SF	5 m (16.4 ft)			
BC-M12F8A-24-8-SF	8 m (26.25 ft)			
BC-M12F8A-24-10-SF	10 m (30.81 ft)			
BC-M12F8A-24-15-SF	15 m (49.2 ft)			

Specifications

Current Rating

2 A

Voltage Rating

30 V

Installation

Static: 10× the outside diameter

Dynamic: 15× the outside diameter

AWG

24 AWG

Outer Diameter

5.6 mm

Shielding

Shielding: Aluminum foil, facing in 25% minimum, 100% coverage

Drain: 22 AWG Drain

Coding

A

Construction

Coupling nut material: Nickel-plated brass

Contact carrier: Black nylon

Connector body: Black PUR

Jacket material: Black PVC

Vibration and Mechanical Shock

Meets IEC 60068-2-6 requirements (Vibration: 10 Hz to 500 Hz; 0.35 mm amplitude, 6-hour sweep cycle, 10 sweep cycles)

Meets IEC 60068-2-27 requirements (Shock: 50G, half-sine wave, 11 ms duration)

Connections

Integral 8-pin M12 female quick disconnect



Operating Conditions

Operating temperature: -40 °C to +50 °C (-40 °F to +122 °F)
Storage temperature: -40 °C to +70 °C (-40 °F to +158 °F)

90% at +50 °C maximum relative humidity (non-condensing)

Environmental Rating

IP66, IP67, IP68

Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to:
www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.