

Connector Location A

Connector Location B

Mating face acc. to IEC 61076-3-124

Mating face RJ45 acc. to IEC 60603-7

X

Y

approx. 62

approx. 45

Ø6,6

IP20 RJ45 DualBoot, Cat. 6A, 8-pole

Mini PushPull ix Industrial Cat.6A, 10-pole, Type A IDC, overmolded (IP65/67)




Black overmolded body

Yellow protection latch with HARTING logo

X
male

Loading Plan
acc. to TIA/EIA 568B

Y
male



Contacts 3 and 8
are not connected

- Temperature range: -40°C ... +70°C

6.0 to 100	±1%
0.6 to 5.9	+0.04
0.2 to 0.5	+0.02
a [m]	Tolerance

length in "1m" step	100	XXX=000
	99	XXX=990
	.	.
	12	XXX=120
length in "0.1m" step	11	XXX=110
	10	XXX=100
	9.9	XXX=099
	9.8	XXX=098
	.	.
	0.5	XXX=005
Step	0.4	XXX=004
	0.3	XXX=003
	0.2	XXX=002
Step	a [m]	XXX

HARTING outd. Cat.6A
4x2xAWG 26/7 PVC black

33483447806XXX

Type of cable

Part no.

NOTE:

* Cat.6A 10 Gbit/s Ethernet transmission possible for lengths up to 45m

For lengths < 1.0m:

- relative positioning of the connectors to each other will be as presented in the drawing,
however with an admissible angular deviation around cable axis of ± 30°

For lengths ≥ 1.0m:

-relative positioning of the connectors to each other not obligatory

All Dimensions in mm		Tech. Character.		Free size tol.		According to production drawing	
All rights reserved		Created by STOCHECIC Stocheci		Inspected by COSTEA Costea		Standardisation MUNTEANV Muntean	
Department HCS - RO		Title MPP ix Type A - RJ45 IP20 Cat6A PVC out		Date 2023-04-13		State Final Release	
HARTING Customised Solutions D-32339 Espelkamp		Type TB		Number 33483447806XXX		Doc-Key / ECM-Nr. 101059480/UGD/001/A 500000241490	
				Rev. A		Page 1/1	