

3ft (1m) DB9 to 3.5mm Serial Cable for Serial Device Configuration, RS232 DB9 Male to 3.5mm Cable Used for Calibrating Projectors, Digital Signage, TVs via Audio Jack

Product ID: 9M351M-RS232-CABLE



This serial cable features male DB-9 and 3.5mm connectors. It enables remote serial RS232 calibration of TVs, projectors, and digital signage devices that feature a 3.5mm audio jack.

High Quality Construction

The aluminum-mylar cable shielding and metal shell connectors mitigate EMI. The molded PVC connectors with strain reliefs and PVC cable jacket prevent damage caused by strain and/or abrasion.

Secure the DB-9 connector by tightening the integrated thumbscrews. These connector screw locks prevent accidental disconnection which could lead to data loss/corruption.

DB9 Serial to 3.5mm Pinout

DB9 Pin 3 to 3.5mm Tip

DB9 Pin 2 to 3.5mm Ring

DB9 Pin 5 to 3.5mm Sleeve

This product is backed for life, including free lifetime 24/5 multi-lingual technical assistance.

Certifications, Reports and Compatibility



Applications

Features

- **DB9 TO 3.5 MM SERIAL CABLE:** 3ft (1m) RS232 serial control cable enables configuration or calibration of a 3.5mm RS-232 serial devices - Use with TVs, projectors, digital signage displays requiring 3-conductor RS-232 serial control through 3.5mm audio jack
- **QUALITY CONSTRUCTION:** High quality 28 AWG copper wires with Al-Mylar cable shielding and shielded metal shell connectors prevent EMI interference - Molded PVC connectors with strain reliefs and PVC jacket prevent damage due to bends or rough usage
- **COMPATIBILITY:** The DB9 to 3.5mm cable works with USB-A and USB-C to DB9 serial adapters (1P3FP-USB-SERIAL / ICUSB232C) for computers that do not have a built-in serial port Note: DB9 gender changer may be required such as our GC9SF (not included)
- **SPECIFICATIONS:** Length: 3.3ft (1m) - DB9 Male to 3.5 mm Male Serial Cable - Color: Black - 28 AWG - OD: 3.5mm - Jacket: PVC - DB9 Pin 3 to 3.5mm Tip - DB9 Pin 2 to 3.5mm Ring - DB9 Pin 5 to 3.5mm Sleeve
- **THE IT PRO'S CHOICE:** Designed and built for IT Professionals, this product is backed for life, including free lifetime 24/5 multi-lingual technical assistance

Hardware

| | |
|-----------------------|----------|
| Warranty | Lifetime |
| Number of Conductors | 3 |
| Connector Plating | Nickel |
| Cable Jacket Material | PVC |

Performance

| | |
|---------------------|--------------|
| Supported Protocols | RS232 Serial |
|---------------------|--------------|

Connector(s)

| | |
|-------------|-----------------------------|
| Connector A | 1 - DB-9 (9 pin, D-Sub) |
| Connector B | 1 - 3.5mm Stereo Male 4 pos |

Environmental

| | |
|-----------------------|-------------------------|
| Operating Temperature | -20 to 60C (-4 to 140F) |
| Storage Temperature | -20 to 60C (-4 to 140F) |
| Humidity | 30 ~ 75% |

Physical

Characteristics

| | |
|-------------------|-----------------|
| Color | Black |
| Connector Style | Straight |
| Wire Gauge | 28 AWG |
| Cable Length | 3.3 ft [1 m] |
| Product Length | 3.4 ft [1.0 m] |
| Product Width | 1.3 in [3.3 cm] |
| Product Height | 0.6 in [1.5 cm] |
| Weight of Product | 1.4 oz [41.0 g] |

Packaging Information

| | |
|---------------------------|------------------|
| Package Quantity | 1 |
| Package Length | 8.7 in [22.0 cm] |
| Package Width | 5.0 in [12.8 cm] |
| Package Height | 0.4 in [1.0 cm] |
| Shipping (Package) Weight | 0.8 oz [23.0 g] |

What's in the Box

| | |
|---------------------|-------------------------------------|
| Included in Package | 1 - DB9 to 3.5mm RS232 Serial Cable |
|---------------------|-------------------------------------|

****Product appearance and specifications are subject to change without notice.***