THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR SHOWN WITHOUT WRITTEN PERMISSION.

| ITEM | CONNECTOR PART NO. | DESCRIPTION |
|---|---|---|
| 1 | See Table 1 | SR CONNECTOR |
| 2 | UL1571, 30 AWG | BLACK |

| IPI CHECK | EOR CHECK |
|---|---|
| | |

Applicable Tooling

BCD

TABLE 1

| ITEM | NUMBER OF CIRCUITS | CONNECTOR PART NO. | ASSEMBLY PART NUMBER | TOTAL WIRE REQUIRED |
|---|---|---|---|---|
| 1 | 2 | 02SR-3S | A02SR02SR30K152A | 304.8 |
| 1 | 3 | 03SR-3S | A03SR03SR30K152A | 457.2 |
| 1 | 4 | 04SR-3S | A04SR04SR30K152A | 609.6 |
| 1 | 5 | 05SR-3S | A05SR05SR30K152A | 762.0 |
| 1 | 6 | 06SR-3S | A06SR06SR30K152A | 914.4 |
| 1 | 7 | 07SR-3S | A07SR07SR30K152A | 1,066.8 |
| 1 | 8 | 08SR-3S | A08SR08SR30K152A | 1,219.2 |
| 1 | 9 | 09SR-3S | A09SR09SR30K152A | 1,371.6 |
| 1 | 10 | 10SR-3S | A10SR10SR30K152A | 1,524.0 |
| 1 | 11 | 11SR-3S | A11SR11SR30K152A | 1,676.4 |
| 1 | 12 | 12SR-3S | A12SR12SR30K152A | 1,828.8 |
| 1 | 13 | 13SR-3S | A13SR13SR30K152A | 1,981.2 |
| 1 | 14 | 14SR-3S | A14SR14SR30K152A | 2,133.6 |






Electrical Specifications

Current: 0.7A DC

Voltage: 50V DC

| REV. | DESCRIPTION | DATE | BY |
|---|---|---|---|
| 1 | Add current and voltage specifications | 6/27/2018 | SP |

SCALE: 1: 1

DIMENSIONS: All dimensions are in MM with a tolerance of +/- 3.0 unless otherwise specified.

DRAWN BY: STEVEN PILKINGTON

CHECKED BY: JUSTIN BAKER

CUSTOMER NAME:

CUSTOMER PART NO.:

DESCRIPTION: 1.0 mm Pitch SR Standard Catalog Assembly - 6" Overall Length – Pin out: 1 to 1

ASSEMBLY PART NO.: SEE TABLE 1

DRAWING NO. & REVISION: GAM-011

REVISED: 2/25/2016