


C84D02UXXX

(M8 Cordset, 4 Position, 24 AWG Unshielded PVC, Female Right Angle to Open End)

FEMALE FACE VIEW





- $\begin{array}{c} 1 \rightarrow \mathsf{BROWN} \\ 2 \rightarrow \mathsf{WHITE} \end{array}$
- 2 → WITE
- $3 \rightarrow BLUE$
- 4 → BLACK

Toll Free: 800.955.2629

Phone: 330.780.2525

Fax: 330.780.2524

- Mueller's C84D02UXXX is an M8 4-pin single ended, unshielded instrumentation cable with a right angle female connector on one end and an open stripped end on the other.
- Keyway A Coding
- Utilizes a 4-conductor 24 AWG PVC-insulated, black cable.
- Ratings:
 - o Current: 3 A
 - o Voltage: 30 V AC/DC
- Material:
 - Coupling Nuts Nickel Plated Brass
 - o Pins/Contacts Gold Plated Brass
- Length: The "U" in the model number represents unit of measurement. Either: Meters (M), Feet (F)
- Length: The "XXX" in the model number represents length. Standard lengths are 2, 5, and 10 meters. Any other lengths available upon request.
- Meets Standard: IEC 61076-2-101
- Protection Class: IEC IP68
- RoHS 3 Compliant