

4 and 5-Pin Receptacles, Rear Mount with Solder Cups

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A (4 & 5 pole)
- 60 VAC/75 VDC, 2 A (6 pole)



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>FKFDL ..</p> <p>Typical panel cutout is 15.3 x 14 mm.</p>	FKFDL 4.4	FSFDL 4.4	Accepts 18 AWG max Leads, 105°C, mates with 4-pin cordsets	<p>Female</p> <p>Male</p>
<p>FSFDL ...*</p> <p>Typical panel cutout is 15.3 x 14 mm.</p>	FKFDL 4.5	FSFDL 4.5	Accepts 18 AWG max Leads, 105°C, mates with 5-pin cordsets	<p>Female</p> <p>Male</p>
<p>FSFDL ...*</p> <p>Typical panel cutout is 15.3 x 14 mm.</p>	FKFDL 6	FSFDL 6	Accepts 22 AWG max Leads, 105°C, mates with 6-pin cordsets	<p>Female</p> <p>Male</p>

Standard housing material is nickel plated brass "FSFDL.."; "FSFDLV.." indicates stainless steel.