



Pushing Performance  
Since 1945

# M12 X-cod 8-pol st m - RJ45 PUR 10m



Image is for illustration purposes only. Please refer to product description.

Part number	09 48 C0C 1756 100
Specification	M12 X-cod 8-pol st m - RJ45 PUR 10m
HARTING eCatalogue	<a href="https://harting.com/0948C0C1756100">https://harting.com/0948C0C1756100</a>

## Identification

Category	System cabling
Series	Circular connectors M12 RJ45
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	M12 X-coding Male Straight
Connector 2	RJ45
Type of cable	Copper cable (round)

## Version

Cable length	10 m
Number of cores	8
Core structure	4x 2x AWG 26/7
Shielding	Shielded
Coding	X-coding

## Technical characteristics

Transmission characteristics	Cat. 6A Class E <sub>A</sub> up to 500 MHz
Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s



**Pushing Performance**  
Since 1945

## Technical characteristics

Limiting temperature	-40 ... +80 °C moved
	-40 ... +80 °C unmoved
Cable diameter	6.7 mm ± 0.3 mm

## Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	Yellow

## Specifications and approvals

Specifications	UN/ECE-R 118 fire protection for rolling stock
----------------	--

## Commercial data

Packaging size	1
Net weight	500 g
Country of origin	China
European customs tariff number	85444290
GTIN	5713140267213
ETIM	EC002599
eCl@ss	27060390 Ready-made data cable (unspecified)