

M12 T-cod 4-pol st/- f/- PUR 5,0m



| Part number | 21 34 370 0446 050 |
|--------------------|------------------------------------|
| Specification | M12 T-cod 4-pol st/- f/- PUR 5,0m |
| HARTING eCatalogue | https://harting.com/21343700446050 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | System cabling |
|---------------|------------------------------|
| Series | Circular connectors M12 |
| Element | Cable assemblies |
| Specification | Pre-assembled on one side |
| Connector 1 | M12 T-coding Female Straight |
| Type of cable | Copper cable (round) |

Version

| Cable length | 5 m |
|-----------------|-------------------|
| Number of cores | 4 |
| Core structure | 4x 1.5 mm² |
| Coding | T-coding T-coding |

Technical characteristics

| Rated current | 12 A |
|----------------------|------------|
| Rated voltage | 63 V DC |
| Limiting temperature | -25 +80 °C |
| Cable diameter | 7.2 mm |

Material properties

| Material (cable) | PUR (polyurethane) |
|------------------|--------------------|
| Colour (cable) | Black |



Material properties

| RoHS | compliant with exemption |
|--------------------------------------|--|
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | 567c8b78-5fa0-43aa-a4c0-beb9d99b7769 |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |

Specifications and approvals

Commercial data

| Packaging size | 1 |
|--------------------------------|--|
| Net weight | 490 g |
| Country of origin | Germany |
| European customs tariff number | 85444290 |
| GTIN | 5713140815858 |
| eCl@ss | 27060390 Ready-made data cable (unspecified) |
| ETIM | EC002599 |
| UNSPSC 24.0 | 26121600 |