

M17 MA str molded 17p PVC open end,10m



Part number	21 37 510 0F04 100
Specification	M17 MA str molded 17p PVC open end,10m
HARTING eCatalogue	https://harting.com/21375100F04100

Image is for illustration purposes only. Please refer to product description.

Identification

Category	System cabling
Series	Circular connectors M17
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	M17 Overmoulded Male Straight
Type of cable	Copper cable (round)
Version	
Cable length	10 m
Number of cores	17
Core structure	17x AWG 22
Technical characteristics	
Rated current	2 A
Rated voltage	60 V
Limiting temperature	-20 +80 °C
Degree of protection acc. to IEC 60529	IP65 IP67
Material properties	
Material (cable)	PVC
Colour (cable)	Black

Page 1 / 2 | Creation date 2025-03-12 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com



Commercial data

Packaging size	1
Country of origin	China
European customs tariff number	85444290
GTIN	5713140240834
eCl@ss	27060311 Assembled sensor actuator-line
ETIM	EC001855
UNSPSC 24.0	26121604

Page 2 / 2 | Creation date 2025-03-12 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com