



USB Sync/Charge Cable with Apple 30-Pin Dock Connector, White, 3 ft. (0.91 m)

MODEL NUMBER: M110-003-WH



Charge and sync your Apple 30-pin iPhone, iPad or iPod using the USB port on your computer.

Description

The M110-003-WH USB Sync/Charge Cable connects your iPhone, iPad or iPod with the USB port on any computer, so you can charge your Apple device and transfer data. This 3-ft. (0.91 m) cable is MFicertified for use with the latest generation of iPhone, iPad and iPod devices.

Features

Syncs and Charges Your Apple 30-Pin Electronic DevicesMFi-certified for use with the latest generation of iPhone, iPad and iPod devices)

Compact and Convenient to UseConnects your 30-pin iPhone, iPad or iPod device and the USB port on your computer or wall chargerWorks with all computers

Highlights

- Features an Apple-compatible 30-pin plug and a USB-A plug
- · Works with any computer
- MFi-certified for broad compatibility with your Apple iPhone, iPad or iPod
- Compatible with all Apple devices with 30-pin connectors

System Requirements

- USB-equipped computer or charger
- iPhone, iPad, iPad mini, iPad mini 2, iPad mini 3, iPad mini 4, iPad Air, iPad Air 2, iPad Pro 12.9 inch, iPad Pro 10.5 inch, iPad Pro 9.7 inch and iPod Touch devices with Lightning port

Package Includes

 M110-003-WH USB Sync/Charge Cable with Apple 30-Pin Dock Connector

Specifications

OVERVIEW		
UPC Code	037332190062	
Technology	USB 2.0 (High Speed)	
Cable Type	Passive	
INPUT		
Maximum Input Amps	2	
POWER		
USB Power Delivery (PD) Charging	No	





CONNECTIONS		
Side A - Connector 1	USB A (MALE)	
Side B - Connector 1	30 PIN APPLE (MALE)	
Connector Plating	Nickel	
Contact Plating	Gold	
Connector Style	Straight	
CHARGING		
Total Charging Watts	10.5	
PHYSICAL		
Material of Construction	PVC	
Cable Jacket Color	White	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	2.8mm	
Cable Length (ft.)	3	
Cable Length (m)	0.91	
Shipping Dimensions (hwd / in.)	5.20 x 0.90 x 2.60	
Shipping Dimensions (hwd / cm)	13.21 x 2.29 x 6.60	
Shipping Weight (lbs.)	0.10	
Shipping Weight (kg)	0.05	
Unit Packaging Type	Вох	
ENVIRONMENTAL		
Operating Temperature Range	-4° to 140°F (-20° to 60°C)	
Storage Temperature Range	-4° to 176°F (-20° to 80°C)	
Relative Humidity	0% to 90% RH, Non-Condensing	
Operating Humidity Range	0% to 90% RH, Non-Condensing	
Storage Humidity Range	0% to 90% RH, Non-Condensing	
Power Provided to Connected Device(s)	10.5W (5V/2.1A)	
FEATURES & SPECIFICATIONS		
USB Specification	USB 2.0 (up to 480 Mbps)	
Data Transfer Rate	480 Mbps	
Angled Plug	No	





STANDARDS & COMPLIANCE		
Product Certifications	MFi	
Product Compliance	RoHS: REACH	
Froduct Compliance	NOTO, REACTI	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	2-year limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.