

USB-A to RJ45 Serial Rollover Cable (M/M) - Cisco Compatible, 250 Kbps, 6 ft. (1.83 m), Gray

MODEL NUMBER: U209-006-RJ45-X



Connects your computer or laptop's USB port to your Cisco modem, router, firewall, switch or other serial-based Cisco device with a console port.

Features

Connects Computer's USB Port to Cisco Device Connect computer or laptop to Cisco modem, router, firewall, switch or other serial-based Cisco device with a console port
Works with older and new Cisco models
6 ft. long

Top-of-the-Line Performance Supports data transfer rates up to 250 Kbps
Supports remote wake-up and power management
Utilizes FTDI chipset.

Easy to Use No other cables or adapters needed
No external power required
Driver CD included (drivers also available online for download if your computer has no CD drive)

Highlights

- Supports data transfer rates up to 250 Kbps
- Supports remote wake-up and power management
- Compatible with Windows, Mac and Linux
- No cables, adapters or external power required

System Requirements

- Computer with available USB port
- Cisco device with available RJ45 console port
- Windows, Mac or Linux operating system

Package Includes

- U209-006-RJ45-X USB to RJ45 Cisco Serial Rollover Cable
- Owner's manual

Specifications

OVERVIEW	
UPC Code	037332190017
CONNECTIONS	
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	RJ45 (MALE)
Connector Plating	Gold
PHYSICAL	
Color	Gray
Material of Construction	PVC
Cable Jacket Color	Gray



Powering Business Worldwide

TRIPP LITE
SERIES

Cable Jacket Material	PVC
Cable Outer Diameter (OD)	2.5 mm
Wire Gauge (AWG)	26
Cable Length (ft.)	6
Cable Length (m)	1.83
Cable Length (in.)	72
Shipping Dimensions (hwd / in.)	1.20 x 4.70 x 4.10
Shipping Dimensions (hwd / cm)	3.05 x 11.94 x 10.41
Shipping Weight (lbs.)	0.24
Shipping Weight (kg)	0.11
Unit Packaging Type	Box
Unit Weight (lbs.)	0.2425
Unit Weight (kg)	0.11
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Storage Temperature Range	-4° to 140°F (-20° to 60°C)
Relative Humidity	0% to 90% RH (Non-Condensing)
FEATURES & SPECIFICATIONS	
IP68 Rated	No
IP20 Rated	No
Driver Required	Yes
STANDARDS & COMPLIANCE	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.