

Ratings

Voltage: 600 V
Temperature: -40~105 °C
Flammability: VW-1

Conductor


Conductor count: 2
Gauge: 22 AWG 0.34 mm²
Material: tinned copper strands
Strand size: Ø 0.16 mm x 17
Resistance at 20 °C: 59.4 Ω /km max

Outer jacket

Material: mPPE
Color: white and black
Diameter: 3.2 ± 0.2 mm (1.6±0.1x 2)
Nominal thickness: 0.38 mm
Insulation resistance at 20 °C: 0.75 MΩ /km min

Wire marking:

E339579 UL AWM STYLE 21516 22 AWG 105°C 600V VW-1 --- cUL
AWM I A/B 105°C 600V FT1 Tensility



Revision:	Date:	Description:	Prepared:	Notes: RoHS compliant Phthalate and halogen free	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com		
A	04/19/2023	Initial release	Verified:				
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Wire, 2C TS, 22 AWG, UL21516, 600V, 105C, 3.2 mm, VW-1, mPPE, white and black	Size:	Part number:	
					A	30-03176	
					Scale: 20:1		Sheet 1 of 1

5

↑

4

3

2

1