

Ratings

Voltage: 300 V

Temperature: -25 ~ 80 °C

Flammability: VW-1

Conductor

Conductor count: 4

Gauge: 26 AWG 0.14 mm²

Material: tinned copper strands

Strand size: $\phi 0.16 \times 7$

Resistance at 20 °C: 150 Ω /km max

Insulator

Material: PVC

Color: red, black, white, green

Diameter: $\phi 1.1 \pm 0.10$ mm

Nominal thickness: 0.29 mm

Resistance at 20 °C: 10 M Ω /km min

Outer jacket

Material: PVC, 80 A

Color: black

Diameter: $\phi 4.25 \pm 0.20$ mm

Nominal thickness: 0.80 mm

Wire marking: E339579 UL AWM STYLE 2464 26 AWG 80°C
300V VW-1 --- cUL AWM I/II A 80°C 300V FT1 TENSILITY

Tests

Insulation tensile strength: 2.11 kgf/mm²

Jacket tensile strength: 1.05 kgf/mm²

After aging at 113 ± 2 °C for 7 days:



Minimum tensile strength 70 % original

Minimum elongation 65 % original

Heat shock: 121 ± 1 °C /1 hour, no observed degradation

Deformation: 121 ± 1 °C /1 hour, ≤ 50 %

Cold bend: -10 ± 2 °C /1 hour, no observed cracking



Revision:	Date:	Description:	Prepared:	Notes: RoHS and REACH compliant	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com		
A	10/31/2023	Initial release	Verified:				
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Function test: no open, no short circuit, no intermittent	Description: Wire, 4C TS, 26 AWG, UL2464, 300V, 80C, 4.25 mm, VW-1, PVC		
					Size: A	Part number: 30-03362	
					Scale: 10:1		Sheet 1 of 1

5

4

3

2

1