

Ratings

Voltage: 300 V
Temperature: -40~105 °C
Flammability: VW-1

Conductor

Conductor count: 4
Gauge: 16 AWG 1.3 mm²
Material: tinned copper strands
Strand size: $\varnothing 0.12 \times 115$
Resistance at 20 °C: 14.6 Ω /km max

Insulator

Material: FEP
Color: red, black, white, green
Diameter: $\varnothing 1.9 \pm 0.10$
Nominal thickness: 0.15 mm
Resistance at 20 °C: 10 M Ω /km min

Filler

Material: aramid fiber



Wrap

Material: cotton paper

Outer jacket

Material: TPE
Color: black
Diameter: $\varnothing 6 \pm 0.25$
Nominal thickness: 0.6 mm

Wire marking: E339579 UL AWM STYLE 21296 16 AWG 105°C
300V VW-1 --- cUL AWM I A 105°C 300V FT1 TENSILITY DGT



Revision:	Date:	Description:	Prepared:	Notes: RoHS compliant Phthalate free Function test: no open, no short circuit, no intermittent	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com		
A	11/01/2023	Initial release	Verified:				
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Wire, 4C TS, 16 AWG, UL 21296, 300V, 105C, 6.0 mm, TPE	Size: A	Part number: 30-03393	
					Scale: 15:1		Sheet 1 of 1

5

4

3

2

1