



Product: <u>5200UE</u> ☑

Security & Sound, 2 Conductor 16 AWG, BC, CMR

Product Description

Security & Commercial Audio Cable, Riser-CMR, 2-16 AWG stranded bare copper conductors with polypropylene insulation, PVC jacket with ripcord

Technical Specifications

| Product Ov | erview/ | | | | | |
|--|-----------------|--|----------|-----------------|-------------|------------|
| Suitable Applie | Data C | Data Circuits, Monitor/Detection, Control Circuits, Initiating Circuits, Notification Circuits | | | | |
| Constructi | on Details | | | | | |
| Conductor | | | | | | |
| Element | No. of Eleme | nts Size | Strandi | ng Mate | rial | |
| Conductor(s) | 2 | 16 AWG | 19x29 | BC - Bare | Copper | |
| Insulation | | | | | | |
| Element | Material | Nom. Thic | kness | Nom. Insulati | ion Diamete | Color Code |
| Conductor(s) | PO - Polyolefi | n 0.008 in (0. | 20 mm) | 0.073 in (1.9 r | mm) | Black, Red |
| Outer Jacket | | | | | | |
| Mater | ial N | om. Thicknes | Nor | n. Diameter | Ripcord | |
| PVC - Polyvin | yl Chloride 0.0 | 17 in (0.43 mr | n) 0.180 |) in (4.57 mm) | Yes | |
| Overall Cable Diameter (Nominal): 0.180 in (4.57 mm) | | | | | | |
| Electrical Characteristics | | | | | | |
| Electrical | maraotorio | 1100 | | | | |
| Electricals | | | | | | |

| Element | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Max. Current |
|--------------|--------------------|-------------------------------|--------------------------------|
| Conductor(s) | 4.2 Ohm/1000ft | 23 pF/ft (75 pF/m) | 6.25 Amps per conductor @ 25°C |

Voltage

UL Voltage Rating 300 V (CMR)

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|-----------------------|----------------|
| 75°C | -20°C to +75°C |

Bend Radius

| Stationary Min. Ins | stallation Min. |
|---------------------------|-------------------|
| 1.8 in (46 mm) 1.8 | 3 in (46 mm) |
| 1.0 1 (40 1 1) 1.0 | 3 111 (40 111111) |
| Max. Pull Tension: | |
| Bulk Cable Weight: | |

Standards and Compliance

| Environmental Suitability: | Indoor - Riser, Indoor |
|----------------------------------|---|
| Flammability / Reaction to Fire: | UL 1666 Riser, FT4, IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Eca; CPR UKCA Class: Eca |
| NEC / UL Compliance: | Article 800, CMR |
| CEC / C(UL) Compliance: | CMG |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance: | UKCA Mark |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Plenum Number: | 6200UE |

History

| Update and Revision: | Revision Number: 0.511 Revision Date: 02-15-2024 | |
|----------------------|--|--|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC/EAN | Footnote |
|-----------------|-------------|--------------|----------|---------------|----------|
| 5200UE 0101000 | Black | Reel | 1,000 ft | 612825157458 | |
| 5200UE 010U1000 | Black | UnReel | 1,000 ft | 612825421146 | |
| 5200UE 010Z1000 | Black | ReelTuff Box | 1,000 ft | 612825157496 | |
| 5200UE 0061000 | Blue, Light | Reel | 1,000 ft | 612825350187 | |
| 5200UE 001U1000 | Brown | UnReel | 1,000 ft | 612825421108 | |
| 5200UE 001Z1000 | Brown | ReelTuff Box | 1,000 ft | 612825157403 | |
| 5200UE 0011000 | Brown | Reel | 1,000 ft | | |
| 5200UE.00152 | Chrome | Reel | 152 m | 8719605008008 | |
| 5200UE.00305 | Chrome | Reel | 305 m | 8719605008015 | |
| 5200UE 008500 | Gray | Reel | 500 ft | 612825157410 | |
| 5200UE 008U500 | Gray | UnReel | 500 ft | 612825421122 | |
| 5200UE 0081000 | Gray | Reel | 1,000 ft | 612825157434 | С |
| 5200UE 008U1000 | Gray | UnReel | 1,000 ft | 612825157427 | |
| 5200UE 008Z1000 | Gray | ReelTuff Box | 1,000 ft | 612825350194 | |
| 5200UE 0051000 | Green, Dark | Reel | 1,000 ft | 612825350170 | |
| 5200UE 0031000 | Orange | Reel | 1,000 ft | 612825350156 | |
| 5200UE 0021000 | Red | Reel | 1,000 ft | 612825421115 | С |
| 5200UE 002Z1000 | Red | ReelTuff Box | 1,000 ft | 612825350149 | |
| 5200UE 0071000 | Violet | Reel | 1,000 ft | 612825336532 | |
| 5200UE 009U1000 | White | UnReel | 1,000 ft | 612825421139 | |
| 5200UE 0091000 | White | Reel | 1,000 ft | 612825157441 | |
| 5200UE 009Z1000 | White | ReelTuff Box | 1,000 ft | 612825157465 | |
| 5200UE 0041000 | Yellow | Reel | 1,000 ft | 612825350163 | |

© 2025 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.