



Product: [7921A](#)

DataTuff® Cat 5e, 4 Bonded-Pr #24 Sol BC, PO Ins, OS+TC Brd, PVC Jkt, CMR CMX-Outdoor

[Request Sample](#)

Product Description

Industrial Ethernet Cat 5e, 4 Bonded-Pair 24AWG (Solid) Bare Copper, PO Insulation, Overall Beldfoil®+Tinned Copper Braid(70%) Shield, PVC Outer Jacket, CMR CMX-Outdoor

Technical Specifications

Product Overview

|                        |  |
|------------------------|--|
| Suitable Applications: | noisy environment, outdoor, harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc.                                       |
| Patent:                | This product has one or more applicable patents. More information on patents can be found at <a href="https://www.belden.com/patents">https://www.belden.com/patents</a> . |

Construction Details

Conductor

| Element | Size   | Stranding | Material         | No. of Elements |
|---------|--------|-----------|------------------|-----------------|
| Pair(s) | 24 AWG | Solid     | BC - Bare Copper | 4               |

Insulation

| Material        | Color Code   |
|-----------------|--|
| PO - Polyolefin | White/Blue Stripe & Blue, White/Orange Stripe & Orange, White/Green Stripe & Green, White/Brown Stripe & Brown |

|              |     |
|--------------|-----|
| Bonded-Pair: | Yes |
|--------------|-----|

Outer Shield

| Shield Type | Material                | Coverage | Drainwire Type    | Notes   |
|-------------|-------------------------|----------|-------------------|---|
| Tape        | Bi-Laminate (Alum+Poly) | 100%     | 26 AWG (Solid) TC | Two drain wires applied helically for added flexibility |
| Braid       | Tinned Copper (TC)      | 70%      |                   |   |

Outer Jacket

| Material                 | Nom. Diameter    | Ripcord |
|--------------------------|------------------|---------|
| PVC - Polyvinyl Chloride | 0.33 in (8.4 mm) | No      |

|                                   |                  |
|-----------------------------------|------------------|
| Overall Cable Diameter (Nominal): | 0.33 in (8.4 mm) |
|-----------------------------------|------------------|

Electrical Characteristics

Electricals

| Max. Conductor DCR            | Max. Capacitance Unbalance |
|-------------------------------|----------------------------|
| 93.8 Ohm/km (28.6 Ohm/1000ft) | 150 pF/ft                  |

Delay

| Max. Delay  | Max. Delay Skew | Nom. Velocity of Prop. |
|-------------|-----------------|------------------------|
| 538 ns/100m | 45 ns/100m      | 70%                    |

High Frequency

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Min. NEXT [dB] | Min. PSNEXT [dB] | Min. ACR [dB] | Min. PSACR [dB] | Min. ACRF (ELFEXT) [dB] | Min. PSACRF (PSELFEXT) [dB] | Min. RL (Return Loss) [dB] | Min. SRL (Structural Return Loss) [dB] | Max./Min. Input Impedance (unFitted) [Ohm] | Max./Min. Fitted Impedance [Ohm] |
|-----------------|-----------------------------------|----------------|------------------|---------------|-----------------|-------------------------|-----------------------------|----------------------------|--|--|----------------------------------|
| 1               | 2.0 dB/100m                       | 65.3           | 62.3             | 63            | 60              | 63.8                    | 60.8                        | 20                         | 20                                     | 100 ± 15                                   | 95-110                           |
| 4               | 4.1 dB/100m                       | 56.3           | 53.3             | 51            | 49              | 51.7                    | 48.7                        | 23.6                       | 23.6                                   | 100 ± 15                                   | 95-110                           |

|       |              |      |      |      |      |      |      |      |      |          |        |
|-------|--------------|------|------|------|------|------|------|------|------|----------|--------|
| 8     | 5.8 dB/100m  | 51.8 | 48.8 | 46   | 43   | 45.7 | 42.7 | 25.4 | 25.4 | 100 ± 15 | 95-107 |
| 10    | 6.5 dB/100m  | 50.3 | 47.3 | 43   | 41   | 43.8 | 40.8 | 26   | 26   | 100 ± 15 | 95-107 |
| 16    | 8.2 dB/100m  | 47.3 | 44.3 | 39   | 36   | 39.7 | 36.7 | 26   | 26   | 100 ± 15 | 95-107 |
| 20    | 9.3 dB/100m  | 45.8 | 42.8 | 36.5 | 33.5 | 37.7 | 34.7 | 26   | 26   | 100 ± 15 | 95-107 |
| 25    | 10.4 dB/100m | 44.3 | 41.3 | 33.9 | 30.9 | 35.8 | 32.8 | 25.5 | 25.5 | 100 ± 15 | 95-107 |
| 31.25 | 11.7 dB/100m | 42.9 | 39.9 | 31   | 28   | 33.9 | 30.9 | 25   | 25   | 100 ± 15 | 95-107 |
| 62.5  | 17.0 dB/100m | 38.4 | 35.4 | 22   | 19   | 27.8 | 24.8 | 23.5 | 23.5 | 100 ± 15 | 95-107 |
| 100   | 22.0 dB/100m | 35.3 | 32.3 | 14   | 11   | 23.8 | 20.8 | 22.5 | 22.5 | 100 ± 15 |        |

Voltage

| UL Voltage Rating                |
|----------------------------------|
| 300 V (CMR), 300 V (CMX-Outdoor) |

Mechanical Characteristics

Temperature

| UL Temperature | Operating      | Installation   | Storage        |
|----------------|----------------|----------------|----------------|
| 60°C           | -40°C To +75°C | -25°C To +75°C | -40°C To +80°C |

Bend Radius

| Stationary Min.   |
|-------------------|
| 1.32 in (33.5 mm) |

|                    |                |
|--------------------|----------------|
| Max. Pull Tension: | 75 lbs (34 kg) |
| Bulk Cable Weight: | 50 lbs/1000ft  |

Standards and Compliance

|                                       |   |
|---------------------------------------|---|
| Environmental Suitability:            | Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Oil Resistance  |
| Flammability / Reaction to Fire:      | UL1666 Riser, FT4, IEEE 1202 Vertical Tray Flame Test, IEC 60332-1-2  |
| CPR Compliance:                       | CPR Euroclass: Eca; CPR UKCA Class: Eca   |
| NEC / UL Compliance:                  | Article 800, CMR, CMX-Outdoor   |
| CEC / C(UL) Compliance:               | CMX-Outdoor   |
| Data Category:                        | Category 5e   |
| TIA/EIA Compliance:                   | ANSI/TIA-568.2-D Category 5e  |
| Third Party Performance Verification: | Category 5e   |
| ISO/IEC Compliance:                   | ISO/IEC 11801-1, IEC 61156-5  |
| European Directive Compliance:        | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16 |
| UK Regulation Compliance:             | UKCA Mark   |
| APAC Compliance:                      | China RoHS II (GB/T 26572-2011)   |

Product Notes

|        |  |
|--------|--|
| Notes: | EtherNet/IP is a trademark of ControlNet International, Ltd. under license by Open DeviceNet Vendor Association, Inc. Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581. |
|--------|--|

History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.534 Revision Date: 02-03-2025 |
|----------------------|--|

Part Numbers

Variants

| Item #        | Color | Putup Type | Length   | UPC          | Footnote |
|---------------|-------|------------|----------|--------------|----------|
| 7921A 0101000 | Black | Reel       | 1,000 ft | 612825191261 | C        |
| 7921A 0102000 | Black | Reel       | 2,000 ft | 612825191278 | C        |
| 7921A 0061000 | Blue  | Reel       | 1,000 ft | 612825191254 | C        |
| 7921A 0021000 | Red   | Reel       | 1,000 ft | 612825191247 | C        |
| 7921A 1NH1000 | Teal  | Reel       | 1,000 ft | 612825191285 | C        |

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.