

Product Description

Electronic, 2 Conductor 20AWG (7x28) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

Technical Specifications

Product Overview

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v,); low voltage digital control (24v,); line level audio; computer communication; panel wirin
Construction Details	
Conductor	
Element No. of Elements Siz	ze Stranding Material
Pair(s) 1 20 A	
2070	
nsulation	
Element Material	Nom. Thickness Nom. Insulation Diameter Color Code
Pair(s) PVC - Polyvinyl Chlorid	e 0.015 in (0.38 mm) 0.065 in (1.7 mm) Black & Red
Outer Jacket	
Material Nom. 1	Thickness Nom. Diameter
PVC - Polyvinyl Chloride 0.025 in	(0.64 mm) 0.180 in (4.57 mm)
Overall Cable Diameter (Nominal)	: 0.180 in (4.57 mm)
Electrical Characteristics	ŝ
lectricals	
Element Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond Max. Current
Pair(s) 11.1 Ohm/1000ft	24.5 pF/ft (80.4 pF/m) 3.7 Amps per Conductor at 20°C
oltage	
UL Voltage Rating 300 V (CMG)	
lechanical Characteristi	ics
emperature	
UL Temperature Operating	
60°C -20°C to +60°C	
Bend Radius	
Stationary Min. Installation Mir	
	25.2 lbs (11.4 kg)

Environmental Suitability:	Indoor - Plenum, Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	UL 1685 FT4 Loading, FT4
CPR Compliance:	CPR Euroclass: Eca; CPR UKCA Class: Eca
NEC / UL Compliance:	Article 800, CMG
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:

Revision Number: 0.512 Revision Date: 02-03-2025

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC/EAN	Footnote
8205.0030	Chrome	Reel	30 m	8719605018076	
8205.00U152	Chrome	UnReel	152 m	8719605018083	
8205.01152	Chrome	Reel	152 m	8719605018106	
8205.00U305	Chrome	UnReel	305 m	8719605018090	
8205.01305	Chrome	Reel	305 m	8719605018113	
8205 060U500	Chrome	UnReel	500 ft	612825195986	
8205 0601000	Chrome	Reel	1,000 ft	612825196006	С
8205 0605000	Chrome	Reel	5,000 ft	612825196020	

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.