



Product: <u>83322E</u> ☑

Electronic, 2 C #16 Str SPC, TFE Ins, OA SPC Brd, TFE Tape Jkt, MIL-W-16878/4 (Type E)

Request Sample

Product Description

High Temperature Electronic, 2 Conductor 16AWG (19x29) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Tape Outer Jacket, MIL-W-16878/4 (Type E)

Technical Specifications

-

Material Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.077 in (2.0 mm) White, Black Duter Shield Silvered Copper (SC) 85% Duter Jacket Material Coverage PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.197 in (5.00 mm) Overall Cable Diameter (Nominal): 0.197 in (5.00 mm) 0.197 in (5.00 mm)	uitable Applications: MIL-W-16878/4 (Type E) Spec; Extreme High/Low Temperature Environments; up to 600V analog signals & voltage cont
Element No. of Elements Size Stranding Material Conductor(s) 2 16 AWG 19x29 SC - Silvered Copper nsulation Element Material Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) PTFE - Polytetrafluoroethylere 0.011 in (0.28 mm) 0.077 in (2.0 mm) White, Black Duter Shield Silvered Copper (SC) 85% Stilvered Copper (SC) 85% Duter Jacket Nom. Thickness Nom. Diameter Nom. Diameter PTFE - Polytetrafluoroethylere 0.011 in (0.28 mm) 0.197 in (5.00 mm) Overall Cable Diameter (Nominal): 0.197 in (5.00 mm) 0.197 in (5.00 mm)	onstruction Details
Conductor(s) 2 16 AWG 19x29 SC - Silvered Copper nsulation Element Material Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) PTFE - Polytetrafiuroethylene 0.011 in (0.28 mm) 0.077 in (2.0 mm) White, Black Shield Type Material Coverage Braid Silvered Copper (SC) 85% Outer Jacket Nom. Thickness Nom. Diameter PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.197 in (5.00 mm) Overall Cable Diameter (Nominal): 0.197 in (5.00 mm) 0.197 in (5.00 mm)	nductor
Material Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.077 in (2.0 mm) White, Black Outer Shield Shield Type Material Coverage Braid Silvered Copper (SC) 85% Outer Jacket Nom. Thickness Nom. Diameter PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.197 in (5.00 mm) Overall Cable Diameter (Nominal): 0.197 in (5.00 mm) 0.197 in (5.00 mm)	Element No. of Elements Size Stranding Material
Element Material Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.077 in (2.0 mm) White, Black Duter Shield Silvered Copper (SC) 85% Duter Jacket Nom. Thickness Nom. Diameter PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.197 in (5.00 mm) Overall Cable Diameter (Nominal): 0.197 in (5.00 mm)	onductor(s) 2 16 AWG 19x29 SC - Silvered Copper
Material Coverage Shield Type Material Coverage Braid Silvered Copper (SC) 85% Outer Jacket Nom. Thickness Nom. Diameter PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.197 in (5.00 mm)	ulation
Material Coverage Braid Silvered Copper (SC) 85% Outer Jacket Material Nom. Thickness Nom. Diameter PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.197 in (5.00 mm)	Element Material Nom. Thickness Nom. Insulation Diameter Color Code
Material Nom. Thickness Nom. Diameter PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.197 in (5.00 mm) Overall Cable Diameter (Nominal): 0.197 in (5.00 mm)	onductor(s) PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.077 in (2.0 mm) White, Black
MaterialNom. ThicknessNom. DiameterPTFE - Polytetrafluoroethylene0.011 in (0.28 mm)0.197 in (5.00 mm)Overall Cable Diameter (Nominal):0.197 in (5.00 mm)	hield TypeMaterialCoverageraidSilvered Copper (SC)85%
PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.197 in (5.00 mm)	
Overall Cable Diameter (Nominal): 0.197 in (5.00 mm)	
Electrical Characteristics	verall Cable Diameter (Nominal): 0.197 in (5.00 mm)
	ectrical Characteristics
Electricals	

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	4.4 Ohm/1000ft	36 pF/ft (120 pF/m)	60 pF/ft (200 pF/m)	11 Amps per conductor @ 25°C

Voltage

Voltage Rating 600 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
200°C	-65°C to +200°C

Bend Radius

Stationary Min.		Installation Min.
	1.97 in (50.0 mm)	1.97 in (50.0 mm)

Max. Pull Tension:	95.5 lbs (43.3 kg)
Bulk Cable Weight:	33 lbs/1000ft

Standards and Compliance

Sustainability:	CA Prop 65
CPR Compliance:	CPR Euroclass: Eca
NEMA Compliance:	NEMA HP3
Military Compliance:	MIL-W-16878/4 (Type E except stranding), (insulated conductors)
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

A. 1. 1.		
Notes:		

Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

History

Update and Revision:

Revision Number: 0.535 Revision Date: 02-03-2025

Part Numbers

Variants

ltem #	Color	Putup Type	Length	UPC	Footnote
83322E 009100	White	Reel	100 ft	612825204084	E
83322E 009500	White	Reel	500 ft	612825204107	E
83322E 0091000	White	Reel	1,000 ft	612825204091	E

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.