



Product: <u>8444</u> ⊠

Electronic, 4 C #22 Str TC, PVC Ins, PVC Jkt, CMG

😭 Request Sample

Product Description

Electronic, 4 Conductor 22AWG (7x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

Technical Specifications

Product Overview

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v,); low voltage control (24v,); line level audio; voice communications; panel wiring
onstruction Details	
onductor	
Element No. of Elemen	nts Size Stranding Material
Conductor(s) 4	22 AWG 7x30 TC - Tinned Copper
sulation	
Element Materi	ial Nom. Thickness Nom. Insulation Diameter Color Code
Conductor(s) PVC - Polyving	yl Chloride 0.011 in (0.28 mm) 0.050 in (1.3 mm) Black, White, Red, Green
uter Jacket	
Material No	om. Thickness Nom. Diameter
VC - Polyvinyl Chloride 0.0	0.185 in (4.70 mm)
Overall Cable Diameter (Nom	inal): 0.185 in (4.70 mm)
lectrical Characteris	tics
lectricals	
Element Nom. Conduc	
Conductor(s) 17.8 Ohm/100	10ft 34 pF/ft (110 pF/m) 2.4 Amps per Conductor at 25°C
oltage	
UL Voltage Rating	
800 V (CMG), 150 V (AWM 2	576)
echanical Character	ristics
emperature	
JL Temperature Operati	ng
-20°C to +	80°C
end Radius	
Stationary Min. Installation	h Min.
.9 in (48 mm) 1.9 in (48 m	1m)
lax. Pull Tension:	36 lbs (16 kg)

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	UL 1685 FT4 Loading, FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca; CPR UKCA Class: Eca
NEC / UL Compliance:	Article 800, CMG
AWM Compliance:	AWM 2576
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	88444, 82444

History

Update and Revision: Revision Number: 0.515 Revision Date: 02-03-2025

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
8444 060100	Chrome	Reel	100 ft	612825207405	
8444 060500	Chrome	Reel	500 ft	612825207429	
8444 060U500	Chrome	UnReel	500 ft	612825207399	
8444 0601000	Chrome	Reel	1,000 ft	612825207412	С
8444 060U1000	Chrome	UnReel	1,000 ft	612825207382	
8444 0605000	Chrome	Reel	5,000 ft	612825207436	

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.