



Product: <u>8458</u> 🗹

Electronic, 15 C #22 Str TC, PVC Ins, PVC Jkt, CMG

😭 Request Sample

Product Description

Electronic, 15 Conductor 22AWG (7x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

Technical Specifications

Product Overview

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v,); low voltage control (24v,); line level audio; voice communications; panel wiring

Construction Details

Conductor

Element No. of Element		Size Stranding		Material	
Conductor(s)	15	22 AWG	7x30	TC - Tinned Copper	

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code			
Conductor(s)	(s) PVC - Polyvinyl 0.011 in (0.28 Chloride mm) 0.050 in (1.3 mm)		0.050 in (1.3 mm)	Black, White, Red, Green, Orange, Blue, White/Black Stripe, Red/Black Stripe, Green/Black Stripe, Orange/Black Stripe, Blue/Black Stripe, Black/White Stripe, Red/White Stripe, Green/White Stripe, Blue/White Stripe			

Outer Jacket

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chlo	ride 0.040 in (1.0 mm)	0.315 in (8.00 mm)
Overall Cable Diame	ter (Nominal):	0.315 in (8.00 mr

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current	
Conductor(s)	18 Ohm/1000ft	34 pF/ft (110 pF/m)	4.2 Amps per Conductor at 30°C	

Voltage

UL Voltage Rating 150 V (CMG), 150 V (UL AWM 2576)

Mechanical Characteristics

Temperature	
UL Temperature Operating	
80°C -20°C to +80°C	
Bend Radius	
Stationary Min. Installation Min.	
3.2 in (81 mm) 3.2 in (81 mm)	
Max. Pull Tension:	137 lbs (62.1 kg)
Bulk Cable Weight:	64 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor			
Flammability / Reaction to Fire:	UL 1685 FT4 Loading, FT4, IEC 60332-1-2			
CPR Compliance:	CPR Euroclass: Eca			
NEC / UL Compliance:	Article 800, CMG			
AWM Compliance:	AWM 2576			
CEC / C(UL) Compliance:	CMG			
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)			
UK Regulation Compliance:	UKCA Mark			
APAC Compliance:	iance: China RoHS II (GB/T 26572-2011)			

History

Update and Revision:

Revision Number: 0.513 Revision Date: 02-03-2025

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
8458 060100	Chrome	Reel	100 ft	612825208037	
8458 060500	Chrome	Reel	500 ft	612825208051	С
8458 0601000	Chrome	Reel	1,000 ft	612825208044	С
8458 0605000	Chrome	Reel	5,000 ft	612825208068	С

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.