



**Product: 8466** ☑

Electronic, 12 C #18 Str TC, PVC Ins, PVC Jkt, CMG

Request Sample

# **Product Description**

Electronic, 12 Conductor 18AWG (19x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

# **Technical Specifications**

## **Product Overview**

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring

## **Construction Details**

### Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	12	18 AWG	19x30	TC - Tinned Copper

### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	PVC - Polyvinyl Chloride	0.018 in (0.46 mm)	0.080 in (2.0 mm)	Black, White, Red, Green, Orange, Blue, White/Black Stripe, Red/Black Stripe, Green/Black Stripe, Orange/Black Stripe, Blue/Black Stripe, Black/White Stripe

### **Outer Jacket**

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	e 0.040 in (1.0 mm)	0.412 in (10.5 mm)
Overall Cable Diameter	(Nominal):	0.412 in (10.5 mm

## **Electrical Characteristics**

### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Conductor(s)	7.13 Ohm/1000ft	26 pF/ft (85 pF/m)	9.8 Amps per Conductor at 30°C

## Voltage

UL Voltage Rating 300 V (CMG), 300 V (UL AWM 2598)

## **Mechanical Characteristics**

## Temperature

<b>UL Temperature</b>	Operating
60°C	-20°C to +60°C

## Bend Radius

Stationary Min.	Installation Min.		
4 1 in (100 mm)	4.1 in (100 mm)		

Max. Pull Tension:	296 lbs (134 kg)	
Bulk Cable Weight:	113 lbs/1000ft	

## **Standards and Compliance**

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	UL 1685 FT4 Loading, FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMG
AWM Compliance:	AWM 2598
CEC / C(UL) Compliance:	CMG
European Directive Compliance: EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
UK Regulation Compliance: UKCA Mark	
APAC Compliance:	China RoHS II (GB/T 26572-2011)

## History

Update and Revision:	Revision Number: 0.504 Revision Date: 02-03-2025	
----------------------	--	--

### **Part Numbers**

## Variants

Item #	Color	Putup Type	Length	UPC	Footnote
8466 060100	Chrome	Reel	100 ft	612825208297	
8466 060250	Chrome	Reel	250 ft	612825208310	С
8466 060500	Chrome	Reel	500 ft	612825208327	С
8466 0601000	Chrome	Reel	1,000 ft	612825208303	С
8466 0605000	Chrome	Reel	5,000 ft	612825208334	CZ

### © 2025 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.