



# Product: <u>8720</u> ☑

Electronic, 2 C #14 Str TC, PE Ins, OS, PVC Jkt, CM

😭 Request Sample

# **Product Description**

Electronic, 2 Conductor 14AWG (19x27) Tinned Copper, PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CM

## **Technical Specifications**

## Product Overview

Suitable Applications: up to 600V analog signals ; up to				0V analog signals ; up to 60	00V digital control ; line level audio; voice communications; panel wiring
Constru	uction Detail	5			
onducto	r				
Element	No. of Elements	Size	Stranding	Material	
Pair(s)	1	14 AWG	19x27	TC - Tinned Copper	
nsulation	1				
Element	Material	Nom. T	hickness	Nom. Insulation Diameter	or Color Code
Pair(s)	PE - Polyethyler	e 0.032 in	(0.81 mm)	0.140 in (3.56 mm)	Black & Clear
Outer Shi	eld				
Shield Type Material Coverage Drainwire Type					
Tape	Bi-Laminate	(Alum+Poly	r) 100%	16 AWG (19x29) TC	
Outer Jacket					
N	laterial	Nom. Thick	kness No	om. Diameter	
PVC - Polyvinyl Chloride 0.035 in (0.89 mm) 0.355 in (9.02 mm)					
Overall Cable Diameter (Nominal): 0.355 in (9.02 mm)					

#### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Max. Current
Conductor(s)	2.84 Ohm/1000ft	24 pF/ft (79 pF/m)	47 pF/ft (150 pF/m)	58 Ohm	25 Amps per Conductor at 30°C

#### Voltage

UL Voltage Rating 600 V (UL AWM 20253), 300 V (CSA AWM)

## **Mechanical Characteristics**

Temperature	
UL Temperature	Opera

80°C	-20°C to +80°C

#### Bend Radius

Stationary Min.	Installation Min.		
3.6 in (91 mm)	3.6 in (91 mm)		

Max. Pull Tension:	135 lbs (61.2 kg)
Bulk Cable Weight:	64 lbs/1000ft

### **Standards and Compliance**

Environmental Suitability:	Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	UL 1685 UL loading , IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, CL2
AWM Compliance:	AWM 20253
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

#### **History**

Update and Revision:

Revision Number: 0.526 Revision Date: 02-03-2025

## Part Numbers

#### Variants

Item #	Color	Putup Type	Length	UPC/EAN	Footnote
8720.00305	Chrome	Reel	305 m	8719605018533	
8720 060500	Chrome	Reel	500 ft	612825214359	С
8720 060U500	Chrome	UnReel	500 ft	612825214328	
8720 0601000	Chrome	Reel	1,000 ft	612825214335	С
8720.001000	Chrome	Reel	1,000 m	8719605126818	
8720 0602000	Chrome	Reel	2,000 ft	612825214342	С
8720.002000	Chrome	Reel	2,000 m	8719605018526	
8720 0605000	Chrome	Reel	5,000 ft	612825214366	С

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.