



# Product: <u>8771</u> ☑

Electronic, 3 C #22 Str TC, PE Ins, OS, PVC Jkt, CM

😭 Request Sample

# **Product Description**

Electronic, 3 Conductor 22AWG (7x30) Tinned Copper, PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CM

## **Technical Specifications**

## Product Overview

Suitable Applications:	low voltage analog signals (4-20ma, 0-1	10v,); low voltage control (24v,); line level audio; void	e communications; panel wiring
Construction Details			
Conductor			
Element No. of Elements	Size Stranding Material		
Conductor(s) 3	22 AWG 7x30 TC - Tinned Coppe	er	
Insulation			
Element Material	Nom. Thickness Nom. Insulation Di	iameter Color Code	
Conductor(s) PE - Polyethylene	0.017 in (0.43 mm) 0.062 in (1.6 mm)	Black, Red, Clear	
Outer Shield			
Shield Type Material	Coverage Drainwire Type		
Tape Bi-Laminate (Alum+	Poly) 100% 22 AWG (7x30) TC		
Outer Jacket			
Material Nom. 1	Thickness Nom. Diameter		
PVC - Polyvinyl Chloride 0.033 in	ı (0.84 mm) 0.199 in (5.05 mm)		
Overall Cable Diameter (Nominal)	: 0.199 in (5.05 mm)		
Electrical Characteristics			
Electrical Characteristics	) 		
Electricals			
Element Nom. Conductor I	DCR Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s) 17.8 Ohm/1000ft	23 pF/ft (75 pF/m)	41 pF/ft (130 pF/m)	6 Amps per Conductor at 30°C
Voltage			
UL Voltage Rating			
300 V (CM), 300 V (UL AWM 2093	3)		
Mechanical Characteristi			
Temperature	_		
UL Temperature Operating			
60°C -20°C to +60°C	;		
Bend Radius			
Bellu Raulus			
Stationary Min. Installation Min	1		
Stationary Min. Installation Min	36.4 lbs (16.5 kg)		

Bulk Cable Weight:

22 lbs/1000ft

**Standards and Compliance** 

Environmental Suitability:	Indoor			
Sustainability:	CA Prop 65			
Flammability / Reaction to Fire:	UL 1685 UL loading , IEC 60332-1-2			
CPR Compliance:	CPR Euroclass: Eca; CPR UKCA Class: Eca			
NEC / UL Compliance:	Article 800, CM			
AWM Compliance:	AWM 2093			
CEC / C(UL) Compliance:	СМ			
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)			
UK Regulation Compliance:	UKCA Mark			
APAC Compliance:	China RoHS II (GB/T 26572-2011)			

#### **History**

Update and Revision:

Revision Number: 0.535 Revision Date: 02-03-2025

## **Part Numbers**

#### Variants

Item #	Color	Putup Type	Length	UPC/EAN	Footnote
8771.00U152	Chrome	UnReel	152 m	8719605019264	
8771.01152	Chrome	Reel	152 m	8719605019288	
8771 060250	Chrome	Reel	250 ft	612825215738	
8771.00U305	Chrome	UnReel	305 m	8719605019271	
8771.01305	Chrome	Reel	305 m	8719605019295	
8771 060500	Chrome	Reel	500 ft	612825215745	
8771 060U500	Chrome	UnReel	500 ft	612825215707	
8771 0601000	Chrome	Reel	1,000 ft	612825215714	С
8771 060U1000	Chrome	UnReel	1,000 ft	612825215691	
8771.013050	Chrome	Reel	3,050 m	8719605019301	
8771 06010000	Chrome	Reel	10,000 ft	612825215721	CY

#### © 2025 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.