



Product: <u>88444</u> 🗹

Electronic, 4 C #22 Str TC, FEP Ins, FEP Jkt, CMP

😭 Request Sample

Product Description

High Temperature Electronic, 4 Conductor 22AWG (7x30) Tinned Copper, FEP Insulation, FEP Outer Jacket, CMP

Technical Specifications

Product Overview

Suitable Applications:	extreme high/low temperature environments; chemical resistant; outdoor and burial applications; low voltage analog signals (4-20ma, 0-10v,); low voltage control (24v, level audio; voice communications; panel wiring					
Construction Details						
Conductor						
Element No. of Elements Size Stranding Material						
Conductor(s) 4	22 AWG 7x30	22 AWG 7x30 TC - Tinned Copper				
Insulation Element Material Nom. Thickness Nom. Insulation Diameter Color Code						
Conductor(s) FEP - Fluorina	ated Ethylene Propylene	0.007 in (0.18 mm)	0.042 in (1.1 mm)	Black, White, Red, Green		
Outer Jacket						
Material	Nom. Thickn	ess Nom. Diame	ter			
FEP - Fluorinated Ethylene Propylene 0.015 in (0.38 mm) 0.131 in (3.33 mm)						
Overall Cable Diameter (Nominal):	0.131 in (3.33 mm)					

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Conductor(s)	17.8 Ohm/1000ft	18 pF/ft (59 pF/m)	7.2 Amps per Conductor at 30°C

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

Temperature

UL Temperature	Operating
150°C	-20°C to +150°C

Bend Radius

Stationary Min.Installation1.2 in (30 mm)1.2 in (30 mm)	
Max. Pull Tension:	36 lbs (16 kg)
Bulk Cable Weight:	15 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor, Outdoor, Oil Resistance, Burial	
Sustainability:	CA Prop 65	
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum), IEC 60332-1-2	
CPR Compliance:	CPR Euroclass: Eca	
NEC / UL Compliance:	Article 800, CMP	
CEC / C(UL) Compliance:	CMP	
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
UK Regulation Compliance:	UKCA Mark	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	
Non-Plenum Number:	8444	

History

Update and Revision: Revision Number: 0.504 Revision Date: 02-03-2025

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
88444 002100	Red	Reel	100 ft	612825217015	С
88444 002500	Red	Reel	500 ft	612825217039	С
88444 0021000	Red	Reel	1,000 ft	612825217022	С

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.