



Product: <u>9363</u> ☑

High Perform Instr, 1 Tri #22 Str TC, PVC Ins E1, OS, PVC Jkt, PLTC

😭 Request Sample

Product Description

High Performance Instrumentation, 1 Triad 22AWG (7x30) Tinned Copper, PVC Insulation E1 Color Code, Overall Beldfoil® Shield, PVC Outer Jacket, PLTC

Technical Specifications

Product Overview

Product Overview						
Suitable Applications:	Instrumentation, Se	ensors, Valves, Positio	oners, RTD, 4-20mA, 0-10V			
Construction Details						
Conductor						
Element No. of Elements Siz	e Stranding	Material				
Triad(s) 1 22 A	WG 7x30 TC	C - Tinned Copper				
Insulation						
Element Material	Nom. Thickness	Nom. Insulation D	iameter Color Code			
Triad(s) PVC - Polyvinyl Chloride	e 0.017 in (0.43 mm	a) 0.062 in (1.6 mm)	Black , White , Red			
Outer Shield						
Shield Type Material	Coverage	Drainwire Type				
Tape Bi-Laminate (Alum+		22 AWG (7x30) TC				
Outer Jacket						
Material Nom. Thickness Nom. Diameter Ripcord						
PVC - Polyvinyl Chloride 0.037 in (0.94 mm) 0.210 in (5.33 mm) Yes						
Overall Cable Diameter (Nominal): 0.210 in (5.33 mm)						
Electrical Characteristics						
Electricals						
Element Nom. Conductor DCR			n. Capacitance Cond-to-Shield			
Triad(s) 18.2 Ohm/1000ft	26 pF/ft (85 pF/m)	45 p	oF/ft (150 pF/m)	2.8 Amps per Conductor at 25°C		
Voltage						
UL Voltage Rating						
300 V (PLTC, CMG)						

Mechanical Characteristics

Stationary Min.Installation Min.2.1 in (53 mm)2.1 in (53 mm)

emperature	
JL Temperature	Operating
105°C -∹	-30°C to +105°C
Table Notes:	

Max. Pull Tension:	36 lbs (16 kg)
Bulk Cable Weight:	24 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance
Flammability / Reaction to Fire:	UL 1685 UL Loading, FT4, T-29-520, IEEE 1202
NEC / UL Compliance:	Article 725, Article 727, Article 800, CMG, ITC, PLTC
AWM Compliance:	AWM 2464
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:

Revision Number: 0.614 Revision Date: 02-03-2025

Part Numbers

Variants

ltem #	Color	UPC	Footnote
9363 0602500	Chrome	612825239406	
9363 0605000	Chrome	612825239413	CZ
9363 060U1000	Chrome	612825239383	
9363 060U500	Chrome	612825239390	

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.