



Ethernet Cable, Cat5e, Riser, UTP (Unshielded Twisted Pair), 304.8 m, 1000 ft.

# RoHS Compliant

Stock No.: CAT5-3041R-UTP-B



## **FEATURES**

- CMR
- UTP
- 24 AWG
- Solid Copper

#### **Product Description**

1 and 2.5 Gigabit (2.5GBASE-T) speeds up to 328 feet. Bandwidth tested up to 350 MHz. Supports PoE/PoE++ (IEEE 802.3af/at/bt) 4PPoE up to 100W. Solid Copper Conductors ANSI/TIA 568 2.D, RoHS-3 compliant and cETLus certified. Bare copper is superior conductor material for data transmission and PoE use.

## **General Specifications**

Attribute	Value
Terminated/Unterminated	Unterminated
Connector Type	RJ45
Cable Type	Ethernet
Length	304.8m
Gauge	24 AWG
Conductor	Bare Copper
Shield/Unshielded	Unshielded
Voltage Rating	300V
1.0 - 550MHz Impedance (Ω)	100 ± 15
Maximum Operating Frequency	350MHz
Operating & Storage Temp.	-40°C to 75°C   -40°F to 167°F
Installation Temp.	-20°C to 75°C   -4°F to 167°F
Jacket Color	Black





## **Product Drawing**

Insulation	PE	Color of Pairs	
Average Thickness (mm)	0.205	Pair 1	Blue-White/Blue
Min Point Thickness (mm)	0.198	Pair 2	Orange-White/Orange
Conductor Insulation Dia. (±0.02mm)	0.86	Pair 3	Green- White/Green
Twisted Pair Dia. (±0.02mm)	1.72	Pair 4 Brown- White/Brown	
Ripcord	Nylon		
Spline	Not Present	Outle Index	
Polyethylene Tape	Not Present	Cable Jacket	PVC
Shielding	U/UTP	Average Thickness (mm)	0.50
		Min. Point Thickness (mm)  Outer Diameter (±0.2mm)	0.45 <b>4.60</b>
Conductor s	Solid Bare Copper	Odter Didiffeter (20,2mm)	4.00
Size	24AWG		
Conductor Dia. (±0.05mm)	0.46		
Standards Reference		Conductor	Jacket Ripcord
		Insulation	Twisted Pairs
UL-444 / ANSI/TIA CETLUS 568-2.D	ISO/IEC 11801		0

Dimensions: Millimeters (Inches)

#### **Part Number Table**

Part Number	Description
CAT5-3041R-UTP-B	Ethernet Cable, Cat5e, Riser, UTP (Unshielded Twisted Pair), 304.8 m, 1000 ft.

Important Notice: This data sheet and its contents (the "Information") belong to the members of the EASE group of companies (the "Group") or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate, but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. EASE is the registered trademark of Ease Electronics Co., Limited 2019.