

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE
PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE
WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	04/12/2023	HBAKKE	GUTTADAURO

1. CONSTRUCTION:

CONDUCTOR: 10 AWG TINNED COPPER
INSULATION: POLYVINYLCHLORIDE, .020" NOM. WALL THICKNESS
INNER JACKET: NYLON, .004" MIN THICKNESS
SHIELD: NON-WOVEN, COVERAGE ≥25%
JACKET: POLYVINYLCHLORIDE, BLACK, .045" NOM. WALL THICKNESS.
OVERALL CABLE DIAMETER

NOM. DIA.

.116"

.169"

.181"

.504±.016"

2. PHYSICAL PROPERTIES:

TEMPERATURE RATING, MAX 90°C
TEMPERATURE RATING, MIN. -40°C
JACKET IS UV RESISTANT

3. ELECTRICAL CHARACTERISTICS:

DIELECTRIC STRENGTH (kv/1min) 2.0(AC)
VOLTAGE RATING, MAX. 600V
MAX COND D.C. RESISTANCE AT 20°C (Ω/km) ≤3.546

4. REFERENCE STANDARD:

UL1277 & UL1581 & UL83
MEETS (UL) VW-1 FLAME TEST


5. MARKING IN WHITE:

E497465 (UL) TYPE TC-ER THHN 3C 10AWG 90°C DRY/75°C WET
600V SUN RES VW-1 -40°C JHOSIN

6. CONDUCTOR COLOR:

1. RED
2. BLACK
3. BLUE

REGULATORY COMPLIANCE:
EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)



UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0 ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 [5] FRACTIONS ± 1/32 .XX = ± .02 [.5] ANGLES ± 1° .XXX = ± .005 [.13]	APPROVALS	DATE	<div>L-com™</div> <div>an INFINITI® brand</div>		50 High Street, West Mill, North Andover, MA 01845 USA. Phone: 1.800.341.5266 1.978.682.6936		
	DRAWN BY HBAKKE	04/12/2023					
	CHECKED BY DMAY	04/12/2023	CATEGORY				
	APPROVED BY DGUST	04/12/2023	BULK CABLE				
THIRD-ANGLE PROJECTION 	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		PRODUCT DESCRIPTION Shielded Power Bulk Tray Cable, Exposed Run, 3 Conductor 10AWG 600V, TC-ER THHN THWN, UL86 UL1277 UL1581, 90C UV Res VW-1 PVC Black, 1KFT				
	COLOR VARIATIONS MAY OCCUR		SIZE A	CAGE CODE 43321	ITEM NO. PBTC103S	REV. A	
			SCALE: NONE			CAD FILE: PBTC103S.SLDDRW	SHEET 1 OF 1