

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE  
PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE  
WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	04/12/2023	HBAKKE	GUTTADAURO

1. CONSTRUCTION:

CONDUCTOR: 14 AWG TINNED COPPER  
INSULATION: POLYVINYLCHLORIDE, .022" NOM. WALL THICKNESS  
INNER JACKET: NYLON, .004" MIN THICKNESS  
SHIELD: NON-WOVEN, COVERAGE ≥25%  
JACKET: POLYVINYLCHLORIDE, BLACK, .045" NOM. WALL THICKNESS.  
OVERALL CABLE DIAMETER

NOM. DIA.

.076"

.118"

.128"

.362±.012"

2. PHYSICAL PROPERTIES:

TEMPERATURE RATING, MAX 90 °C  
TEMPERATURE RATING, MIN. -40 °C  
JACKET IS UV RESISTANT

3. ELECTRICAL CHARACTERISTICS:

DIELECTRIC STRENGTH (kv/1min) 2.0(AC)  
VOLTAGE RATING, MAX. 600V  
MAX COND D.C. RESISTANCE AT 20 °C (Ω/km) ≤8.96

4. REFERENCE STANDARD:

UL1277 & UL1581 & UL83  
MEETS (UL) VW-1 FLAME TEST


5. MARKING IN WHITE:

E497465 (UL) TYPE TC-ER THHN 2C 14AWG 90 °C DRY/75 °C WET  
600V SUN RES VW-1 -40 °C JHOSIN


6. CONDUCTOR COLOR:

1. RED
2. BLACK

REGULATORY COMPLIANCE:  
EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)



CROSS-SECTIONAL VIEW

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]  OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0  ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 [5]      FRACTIONS ± 1/32 .XX = ± .02 [.5]      ANGLES ± 1° .XXX = ± .005 [.13]	APPROVALS	DATE	<div>L-com™</div> <div>an INFINITI® brand</div>		50 High Street, West Mill, North Andover, MA 01845 USA Phone: 1.800.341.5266 1.978.682.6936	
	DRAWN BY HBAKKE	04/12/2023				
	CHECKED BY DMAY	04/12/2023	CATEGORY	BULK CABLE		
	APPROVED BY DGUST	04/12/2023				
<div>THIRD-ANGLE PROJECTION</div> <div></div>	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		PRODUCT DESCRIPTION Shielded Power Bulk Tray Cable, Exposed Run, 2 Conductor 14AWG 600V, TC-ER THHN THWN, UL86 UL1277 UL1581, 90C UV Res VW-1 PVC Black, 1KFT			
	COLOR VARIATIONS MAY OCCUR	SIZE A	CAGE CODE 43321	ITEM NO. PBTC142S	REV. A	
			SCALE: NONE	CAD FILE: PBTC142S.SLDDRW		SHEET 1 OF 1