

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

	REVISIONS						
REV	DESCRIPTION	DATE	APPROVAL				
Α	INITIAL RELEASE	01/21/2021	GUTTADAURO				

TSFZC7-XXX-XXXF CONSISTS OF A CONTINUOUS LENGTH OF BULK CABLE





DIA: .042+/-.002[1.06+/-.05]

NOTES:

1. CONSTRUCTION:

CONSTRUCTION:
CONDUCTOR: 26 AWG STRANDED BARE COPPER
INSULATION MATERIAL: FOAMED-PE
PAIRS: COLOR CODED SINGLES TWISTED INTO PAIRS
SHIELD (PAIR): AN ALUMINUM POLYESTER FOIL SHIELD, 25% OVERLAPPING (ALUMINUM OUTWARD)
OUTER SHIELD: TINNED COPPER BRAID, 60% COVERAGE
JACKET: LSZH, COLOR SEE CHART
CABLE DIA: 0.236"

CABLE DIA: 0.236" +/- .008 [6.0 +/- 0.20mm]

2. PHYSICAL PROPERTIES:

OPERATING TEMPERATURE RATING: -10 ° C TO +80 ° C STORAGE TEMPERATURE RATING: -20 ° C TO +80 ° C

FLAME TEST: IEC60332-1 CORROSIVE GAS: IEC 60754 SMOKE EMISSION: IEC 61034

3. ELECTRICAL CHARACTERISTICS: VOLTAGE RATING: 30V DIELECTRIC STRENGTH: 500VAC/MINUTE INSULATION RESISTANCE(FOAMED-PE):10M Ω -10m Min. AT 20 ° C CONDUCTOR RESISTANCE(26AWG): $150\Omega/\text{KM}$ Max. AT 20 ° C

- 4. ENVIRONMENT PROTECT STANDARD: RoHS2.0 and REACH COMPLIANT
- 5. JACKET PRINT(WHITE INK ON BLACK JACKET, BLACK INK ON BLUE JACKET): L-COM,INC WWW.L-COM.COM CAT.7 4PR 26AWG S/FTP PATCH CABLE LOW SMOKE ZERO HALOGEN ROHS WW/YY
- 6. PACKAGE:

MODEL NUMBER	LENGTH	JACKET COLOR	PACKAGING		
TSFZC7-BLK-1000F	1000.0 FT	BLACK (RAL9005)	SPOOL		
TSFZC7-BLK-100F	100.0 FT	BLACK (RAL9005)	POLY BAG		
TSFZC7-BLK-500F	500.0 FT	BLACK (RAL9005)	SPOOL		
TSFZC7-BLU-1000F	1000.0FT	BLUE (RAL5017)	SPOOL		
TSFZC7-BLU-100F	100.0 FT	BLUE (RAL5017)	POLY BAG		
TSFZC7-BLU-500F	500.0FT	BLUE (RAL5017)	SPOOL		

		APPROVALS	DATE						
	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]	DRAWN BY B.ZHANG	12/24/2020	L -com [™]				50 HIGH STREET NORTH ANDOVER, MA	
	OVERALL CABLE LENGTH TOLERANCE:	CHECKED BY	10/0//0000		á	an INF	INIT [®] brand	018	345
	≤12 [305] = +1 [25] / - 0	GUTTADAURO	12/24/2020	CATEGO	DRY				
	>12 [305] - 60 [1524] = +2 [51] / -0 >60 [1524] - 120 [3048] = +4 [102] / -0 >120[3048] - 300[7620] = +6 [152] / -0 >300[7620] = +5% / -0% ALL OTHER DIMENSIONAL TOLERANCES:	APPROVED BY GUTTADAURO	12/24/2020	TELECOM/MODULAR					
		CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		PRODUCT DESCRIPTION					
	.X = .2 [5.08] .XX = .02 [.51] .XXX = .005 [.13]			CAT7 S/FTP 4PR/26 STR LSZH JKT					
	PROJECTION (+)	COLOR VARIATIONS MAY OCCUR		SIZE	FSCA 43	и NO. 321	DWG. NO.	TSFZC7	A REV.
	The state of the s			SCALE	: NONE	CADF	ILE: TSFZC7.SLDD	RW	SHEET 1 OF 1