

VFD Cables

VFD XLPE TR Lean

Variable frequency drive - double shielded VFD cable with XLPE insulation
Type TC-ER



Marking for VFD XLPE TR LEAN 35661404:

SAB NORTH AMERICA VFD XLPE TR LEAN P/N 35661404 (UL) Type TC-ER 14AWG/3C XHHW-2 CDRS + GNDG CDR 90C Dry/Wet 600V, Oil Res I & II, Sunlight Resistant, Direct Burial, (UL) WTTC 1000V, (UL) Flexible Motor Supply Cable, c(UL) CIC-TC XLPE 600V FT4, CSA AWM I/II A/B 90C 1000V FT4 RoHS CE

Construction:

Conductor:	tinned copper strands class K
Insulation:	special formulated crosslinked PE, ground wire PVC
Color code:	blackish gray conductors with consecutive white numbers and green/yellow ground
Stranding:	in layers
Shielding:	double shield, AMA foil and tinned copper braiding
Jacket material:	special sunlight and oil resistant copolymer
Jacket color:	black (RAL 9005)

Outstanding features:

- interconnection of variable frequency drive control device to variable frequency motors
- UL 90°C wet
- WTTC: UL subject 2277
- TC-ER: UL standard 1277
- UL flexible motor supply cable 1000 V
- recommended for installations up to 100ft
- Oil Res I & II
- double shielded (100% shielded)
- Class 1 Div 2 per NEC Article 501.4 (B)

Technical data:

Voltage:	(UL) / c(UL): 600 V CSA-AWM: 1000 V (UL) WTTC: 1000 V
Testing voltage:	3000 V
Min. bending radius:	12 x O.D.
Temperature range:	(UL) / c(UL) / CSA-AWM: up to +90°C -40/105°C
static:	
Burning characteristics:	(UL) / c(UL) FT4, c(UL) / CSA-AWM FT1, FT2
Oil resistance I & II:	yes
Sunlight resistance:	yes
Exposed runs:	yes
Cold bend test:	-40°C
Direct burial:	yes
Approvals:	UL TC-ER, UL WTTC, c(UL) CIC-TC, CSA AWM, CE, RoHS
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30

item no.	AWG/c	nominal outer-ø		cable weight ≈lbs/mft
		inch 10%	mm 10%	
▶ 35661804	18/4c	0.383	9.7	94
▶ 35661604	16/4c	0.423	10.7	120
▶ 35661404	14/4c	0.468	11.9	153
▶ 35661204	12/4c	0.530	13.5	207
▶ 35661004	10/4c	0.606	15.4	286
▶ 35660804	8 /4c	0.814	20.7	471

Other dimensions and colors are possible on request.

* UL TC-ER-JP (joist pull) available upon request



- Temperature resistant down to -40°C
- Heavy duty application