



**Product:** [DPLN300](#)

CAT3 Backbone, 300pr, UTP, LS-PVC Jkt, CMP

Product Description

CAT3, DIW 300-Pair, U/UTP-unshielded, Plenum-CMP, Premise Backbone Cable, 24 AWG solid bare copper conductors, LS-PVC insulation, ripcord, LS-PVC jacket

Technical Specifications

Product Overview

Suitable Applications:	Premise Backbone Cable
------------------------	------------------------

Physical Characteristics (Overall)

Conductor			
AWG	Stranding	Material	No. of Pairs
24	Solid	BC - Bare Copper	300
Conductor Count:			600
Total Number of Pairs:			300

Insulation	
Material	
PVC - Polyvinyl Chloride	
Bonded-Pair:	N/A

Number	Color
1	White/Blue & Blue/White
2	White/Orange & Orange/White
3	White/Green & Green/White
4	White/Brown & Brown/White
5	White/Slate & Slate/White
6	Red/Blue & Blue/Red
7	Red/Orange & Orange/Red
8	Red/Green & Green/Red
9	Red/Brown & Brown/Red
10	Red/Slate & Slate/Red
11	Black/Blue & Blue/Black
12	Black/Orange & Orange/Black
13	Black/Green & Green/Black
14	Black/Brown & Brown/Black
15	Black/Slate & Slate/Black
16	Yellow/Blue & Blue/Yellow
17	Yellow/Orange & Orange/Yellow
18	Yellow/Green & Green/Yellow
19	Yellow/Brown & Brown/Yellow
20	Yellow/Slate & Slate/Yellow
21	Violet/Blue & Blue/Violet
22	Violet/Orange & Orange/Violet

23	Violet/Green & Green/Violet
24	Violet/Brown & Brown/Violet
25	Violet/Slate & Slate/Violet
Group One Binder	White/Blue
Group Two Binder	White/Orange
Group Three Binder	White/Green
Group Four Binder	White/Brown
Group Five Binder	White/Slate
Group Six Binder	Red/Blue
Group Seven Binder	Red/Orange
Group Eight Binder	Red/Green
Group Nine Binder	Red/Brown
Group Ten Binder	Red/Slate
Group Eleven Binder	Black/Blue
Group Twelve Binder	Black/Orange

Color Chart 2

Number	Color
1	Blue/White
2	Orange/White
3	Green/White
4	Brown/White
5	Gray/White
6	Blue/Red
7	Orange/Red
8	Green/Red
9	Red/Brown
10	Red/Gray
11	Black/Blue
12	Black/Orange

Outer Jacket

Material	Material Trade Name	Nominal Diameter	Ripcord
PVC - Polyvinyl Chloride	Flamarrest®	1.350 in	Yes

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. DCR Unbalance
93.8 Ohm/km	5 %

Capacitance

Max. Capacitance Unbalance	Nom.Mutual Capacitance
330 pF/100m	17 pF/ft

Delay

Frequency [MHz]	Max. Delay	Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
16 MHz	543 ns/100m	45 ns/100m	61%

High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. RL (Return Loss) [dB]	Max./Min. Fitted Impedance
0.772 MHz	2.2 dB/100m	47.0 dB	43.0 dB	50.1 dB	46.1 dB		
1 MHz	2.6 dB/100m	45.0 dB	41.0 dB	47.8 dB	43.8 dB	12.0 dB	100 ± 15 Ohm
4 MHz	5.6 dB/100m	36.0 dB	32.0 dB	36.0 dB	32.0 dB	12.0 dB	100 ± 15 Ohm
8 MHz	8.5 dB/100m	31.0 dB	28.0 dB	28.3 dB	24.3 dB	12.0 dB	100 ± 15 Ohm
10 MHz	9.7 dB/100m	30.0 dB	26.0 dB	26.2 dB	22.3 dB	12.0 dB	100 ± 15 Ohm
16 MHz	13.1 dB/100m	27.0 dB	23.0 dB	20.1 dB	16.1 dB	10.0 dB	100 ± 15 Ohm

Voltage

UL Voltage Rating
300 V RMS

Temperature Range

Installation Temperature Range:	0°C To +50°C
Non-UL Temp Rating:	+60°C
Storage Temperature Range:	-30°C To +60°C
Operating Temperature Range:	-30°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	1220 lbs/1000ft
Max. Pull Tension:	1800 lbs
Min. Bend Radius During Installation:	27.0 in
Min. Bend Radius/Minor Axis:	13.5 in

Standards

NEC/(UL) Compliance:	CMP
CEC/C(UL) Compliance:	CMP
CPR Euroclass:	Eca
Data Category:	Category 3
ANSI Compliance:	S-90-661-2012 Category 3, ANSI/NEMA WC-63.1 Category 3
TIA/EIA Compliance:	ANSI/TIA-568-C.2 Category 3

Applicable Environmental and Other Programs

Environmental Space:	Plenum
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	Yes
EU CE Mark:	Yes
EU REACH SVHC Compliance (yyyy-mm-dd):	2017-07-10
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	No
Suitability - Oil Resistance:	No
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

Flammability, LS0H, Toxicity Testing

CSA/C(UL) Flammability:	FT6
UL Flammability:	NFPA 262 Plenum (UL 910)
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

Related Part Numbers

Non-Plenum Number:	DIW300
--------------------	--------

Variants

Item #	Color	Put-Up Type	Length	UPC
DPLN300 732CUT	Olive	Cut to Length		612825061038
DPLN300 732CUT	Olive	Cut to Length	1 ft	612825061038

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Print Includes Descending Footage/Meter Markings.
--------	--

History

Update and Revision:	Revision Number: 0.410 Revision Date: 12-19-2022
----------------------	--

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.