




Product: [FRD5TYL](#)



Fiber Raceway Slotted Duct 4x12 with Lid

Product Description

Fiber Raceway Duct & Snap On Lid, 4x12, 2 meters long

Technical Specifications

Product Overview

Environmental Space:	Indoor
----------------------	--------

Construction

Weight:	13.646 lbs
Height:	4.527 in (114.986 mm)
Width:	12.283 in
Length:	78.740 in

Product Material

Materials

Material
Fire retardant plastic, Halogen free, UL94-VO rated

Related Part Numbers

Variants

Item #	Color	Length
FRD5TYL	Yellow	78.740 in

Product Notes

Notes:	It is recommended that a duct be filled to about 50% of its depth with optical fibre cords. Thus, a 300 mm wide duct typically can carry about 5850 of 1.6mm dia optical fibre cords or about 1650 of 3mm dia. optical fibre cords, without causing excessive stress on them. The duct comes complete with a lid and is made of tough Noryl plastic with a non - halogen fire retardent. The cover does not have hinges; it clips onto the duct. The duct connects to other 300mm duct sections and various bends, adapters etc., using the slotless joiner. A duct mounting kit is available separately.
--------	---

History

Update and Revision:	Revision Number: 0.78 Revision Date: 11-09-2022
----------------------	---

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.