

Specification Sheet

Part Number: TELS-24STRAP



Continuous strap and separate heads allow for any bundle diameter, eliminating waste.

Smooth strap prevents cable damage.

24" Extended-Length Tie, POM, Black, 25/pkg

Article Number	111-32109
Type	TELS-24STRAP
Color	Black (BK)
Quantity Per	reel
Product Description	Extended Length Ties provide a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls provide a strong grip on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.
Short Description	24" Extended-Length Tie, POM, Black, 25/pkg

Global Part Name	TELS-24STRAP-POM-BK
------------------	---------------------

Minimum Tensile Strength (Imperial)	250
-------------------------------------	-----

Minimum Tensile Strength (Metric)	1115
-----------------------------------	------

Length L (Imperial)	24.0
---------------------	------

Length L (Metric)	610.0
-------------------	-------

Identification Plate Position	none
-------------------------------	------

Releasable Closure	No
--------------------	----

Tie Closure	steel pawl
-------------	------------

Variant	Endless
---------	---------

Width W (Imperial)	0.5
--------------------	-----

Width W (Metric)	12.7
------------------	------

Material	Polyacetal (POM)
----------	------------------

Material Shortcut	POM
-------------------	-----

Material Cable Tie	Polyacetal (POM)
--------------------	------------------

Material Head	Polyacetal (POM)
---------------	------------------

Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +194°F (-40°C to +90°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	25
Package Quantity (Metric)	25
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)