HellermannTyton

Specification Sheet

Part Number: 115-28589

Article Number

Global Part Name



Manufactured from a soft, tear-resistant thermoplastic polyurethane these ties have several unique features: strong, yet elastic, and suitable for temperatures as low as -20 degrees C.

The SOFTFIX ties are releasable and reusable which is ideal for bundling cables in temporary applications such as musical events, theatres etc.

Cable Tie without Serration, 22.83" Long, Flexible TPU, Black, 10/pkg

Туре	SRT58028
Color	Black (BK)
Quantity Per	pcs.
Product Description	Soft, flexible material makes these ties particulary suitable for use on sensitive wires, such as fibre-optic cables. Additionally the ties are suitable for use on moving or and vibrating applications. The double slotted head allows for parallel bundling.
Short Description	Cable Tie without Serration, 22.83" Long, Flexible TPU, Black, 10/pkg

SRT58028-TPU-BK

115-28589

Minimum Tensile Strength (Metric)	360
Length L (Imperial)	22.83
Length L (Metric)	580
Fixation Method	Releasable Cable Tie
Identification Plate Position	none
Releasable Closure	Yes
Tie Closure	ladder style
Variant	Not Serrated
Width W (Metric)	28.0
Bundle Diameter Max (Imperial)	5.91
Bundle Diameter Max (Metric)	150
Thickness T (Metric)	3.4
Material	Thermoplastic Polyurethane (TPU)
Material Shortcut	TPU

UL 94 HB

Flammability

Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	10
Package Quantity (Metric)	10

3926909988

58.2

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

Customs Number

Weight (Metric)

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions