

Specification Sheet

Part Number: 133-03178



Inverted retaining legs and narrow opening prevent inadvertent disengagement

Controlled flex and angled entry promote easy installation

Robust arrowhead design provides low insertion effort yet delivers exceptional retention strength in a 65 mm hole in panels from 12 to 16 mm

Tube and Pipe Clip with 6.5mm Arrowhead, 4.7-5.1mm Diameter, PA66HIRHS, Black, 4000/ctn

Article Number	133-03178
Type	PC5AH6.5
Color	Black (BK)
Quantity Per	carton
Product Description	This clip features a modular design that can be used individually or lined together to secure multiple pipes or hoses.
Short Description	Tube and Pipe Clip with 6.5mm Arrowhead, 4.7-5.1mm Diameter, PA66HIRHS, Black, 4000/ctn
Global Part Name	PC5AH6.5-PA66HIRHSUV-BK

Length L (Imperial)	0.67
Length L (Metric)	17.0
Fixation Method	Arrowhead
Width W (Metric)	10.0
Bundle Diameter Min (Imperial)	0.18
Bundle Diameter Min (Metric)	4.5
Bundle Diameter Max (Imperial)	0.19
Bundle Diameter Max (Metric)	4.9
Height H (Imperial)	0.86
Height H (Metric)	21.5
Panel Thickness Min (Imperial)	0.05
Panel Thickness Max (Imperial)	0.06
Panel Thickness Min (Metric)	1.2
Panel Thickness Max (Metric)	1.6
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm 6.35 mm (hexagonal)
Disc Diameter (Metric)	17.0

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
 Phone: (800) 537-1512 | Email: corp@htamericas.com