

Specification Sheet

Part Number: 133-03188

Triple pipe clip secures three routings together while keeping them separated, to prevent chafing or heat transfer

Inverted retaining legs and narrow opening prevent inadvertent disengagement of pipe



Controlled flex and angled entry promote easy pipe installation

Tube and Pipe Clip, 3x4.7-5.1mm Diameter, PA66HIRHSUV, Black, 4000/ctn

Article Number	133-03188
Type	PC5X3
Color	Black (BK)
Quantity Per	carton
Product Description	This clip features a modular design that can be used individually or lined together to secure multiple pipes or hoses.
Short Description	Tube and Pipe Clip, 3x4.7-5.1mm Diameter, PA66HIRHSUV, Black, 4000/ctn
Global Part Name	PC5X3-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)	20
Minimum Tensile Strength (Metric)	90
Length L (Imperial)	1.03
Length L (Metric)	25.2
Width W (Imperial)	0.4
Width W (Metric)	10.16
Height H (Imperial)	0.38
Height H (Metric)	9.3
Nominal Diameter (Metric)	4.7
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)

Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.
[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)