

Specification Sheet

Part Number: 133-04044



Secures two routings together while keeping them separated, to prevent chafing or heat transfer

Inverted retaining legs and narrow opening prevent inadvertent disengagement

Controlled flex and angled entry promote easy installation

Robust arrowhead design provides low insertion effort yet delivers exceptional retention strength in a 65 mm hole

For use with routings of the following size: 2x 47-51mm

Tube and Pipe Clip with 6.5mm Arrowhead, 1.2-1.6mm Panel Thickness, PA66HIRHS, Black, 5000/ctn

Article Number	133-04044
Type	PC5X2SO
Color	Black (BK)
Quantity Per	carton
Product Description	This clip features a modular design that can be used individually or lined together to secure multiple pipes or hoses.
Short Description	Tube and Pipe Clip with 6.5mm Arrowhead, 1.2-1.6mm Panel Thickness, PA66HIRHS, Black, 5000/ctn

Global Part Name	PC5X2SO-PA66HIRHS-BK
------------------	----------------------

Length L (Imperial)	0.97
---------------------	------

Length L (Metric)	23.74
-------------------	-------

Fixation Method	Arrowhead
-----------------	-----------

Width W (Imperial)	0.88
--------------------	------

Width W (Metric)	22.35
------------------	-------

Height H (Imperial)	1.14
---------------------	------

Height H (Metric)	28.9
-------------------	------

Panel Thickness Min (Imperial)	0.02
--------------------------------	------

Panel Thickness Max (Imperial)	0.04
--------------------------------	------

Panel Thickness Min (Metric)	0.6
------------------------------	-----

Panel Thickness Max (Metric)	1.0
------------------------------	-----

Mounting Hole Diameter D (Imperial)	0.24" x 0.27
-------------------------------------	--------------

Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
-----------------------------------	--------------

Mounting Hole Diameter D Min (Imperial)	0.24
---	------

Mounting Hole Diameter D Max (Imperial)	0.27
---	------

Mounting Hole Diameter D Max (Metric)	6.9
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	5008
Package Quantity (Metric)	5000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
 Phone: (800) 537-1512 | Email: corp@htamericas.com