

## Specification Sheet

Part Number: 133-04335

Bundling clip allows for routing of a bundle through high heat areas.

Made from Flexible PPS high heat material for exceptional heat and chemical resistance.

6.5x12.5 portable oval hole allows the routing to be secured away from obstructions and sources of heat and or abrasion

Dog bone ends help keep bundling clip from slipping off routing.



Bundling Clip with Arrowhead, 90 Degree Offset, 12.35mm hole dia., 13.5-15.0mm Thickness, PPS, Silver, 2500/ctn

|                     |                                                                                                                           |
|---------------------|---------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 133-04335                                                                                                                 |
| Type                | BCATC90DEG                                                                                                                |
| Color               | Silver (SR)                                                                                                               |
| Quantity Per        | bag                                                                                                                       |
| Product Description | HellermannTyton's bundling clips allow a harness to be routed around a corner and attached to the panel at this location. |
| Short Description   | Bundling Clip with Arrowhead, 90 Degree Offset, 12.35mm hole dia., 13.5-15.0mm Thickness, PPS, Silver, 2500/ctn           |
| Global Part Name    | BCATC90DEG-PPS-SR                                                                                                         |

|                                         |                |
|-----------------------------------------|----------------|
| Length L (Imperial)                     | 2.0            |
| Length L (Metric)                       | 51.0           |
| Offset Length (Imperial)                | 1.47           |
| Offset Length (Metric)                  | 37.5           |
| Fixation Method                         | Arrowhead      |
| Width W (Imperial)                      | 0.62           |
| Width W (Metric)                        | 16.0           |
| Panel Thickness Min (Imperial)          | 0.53           |
| Panel Thickness Max (Imperial)          | 0.59           |
| Panel Thickness Min (Metric)            | 13.5           |
| Panel Thickness Max (Metric)            | 15.0           |
| Mounting Hole Diameter D (Imperial)     | 0.46 - 0.51    |
| Mounting Hole Diameter D (Metric)       | 11.7 - 13.0 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.46           |
| Mounting Hole Diameter D Max (Imperial) | 0.51           |
| Mounting Hole Diameter D Max (Metric)   | 13.0           |

|                              |                             |
|------------------------------|-----------------------------|
| Material                     | Polyphenylene Sulfide (PPS) |
| Material Shortcut            | PPS                         |
| UV Resistant (Yes/No)        | No                          |
| Use Conditions               | For Indoor and Outdoor Use  |
| Reach Compliant (Article 33) | No                          |
| Package Quantity (Imperial)  | 2500                        |
| Package Quantity (Metric)    | 2500                        |
| Customs Number               | 3926909988                  |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)