

Specification Sheet

Part Number: 151-01207



Design provides quick and easy assembly

Isolator mount dampens harmful vibrations on bundles

Material is durable, chemical and abrasion resistant, and remains flexible in low temperatures

Bundling Clip with Edge Clip, 0.04 - 0.12" Panel Thickness, PA66HIRHSUV, Black, 500/pkg

Article Number	151-01207
----------------	-----------

Type	RCEC
------	------

Color	Black (BK)
-------	------------

Quantity Per	carton
--------------	--------

Product Description	HellermannTyton's edge clip and tape clip assembly is ideal for routing bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure, and the extraction force is high due to the integrated metal clamp that holds the edge clip in place. These edge clips include a tape bar, which can be secured to cables with cable ties or tape.
---------------------	---

Short Description	Bundling Clip with Edge Clip, 0.04 - 0.12" Panel Thickness, PA66HIRHSUV, Black, 500/pkg
-------------------	---

Global Part Name	RCEC-PA66HIRHSUV-BK
------------------	---------------------

Length L (Imperial)	2.84
---------------------	------

Length L (Metric)	72.2
-------------------	------

Fixation Method	Edge Clip
-----------------	-----------

Width W (Imperial)	0.79
--------------------	------

Width W (Metric)	20.0
------------------	------

Bundle Diameter Max (Imperial)	1.22
--------------------------------	------

Bundle Diameter Max (Metric)	31.0
------------------------------	------

Height H (Imperial)	1.69
---------------------	------

Height H (Metric)	43.0
-------------------	------

Panel Thickness Min (Imperial)	0.04
--------------------------------	------

Panel Thickness Max (Imperial)	0.12
--------------------------------	------

Panel Thickness Min (Metric)	1.0
------------------------------	-----

Panel Thickness Max (Metric)	3.0
------------------------------	-----

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
 Phone: (800) 537-1512 | Email: corp@htamericas.com