

Specification Sheet

Part Number: 151-02570



- Integrated design allows for easy insertion by hand
- 0.75–1.25 mm panel thickness range allows for multiple applications
- Double-compression design that accommodates various sizes of wire and cable
- Presents a high extraction force for withstanding extreme conditions

Low Profile 90° Metal Edge Clip, 0.76–1.24mm Panel Thickness, 4–7.4mm Cable Range, SS304, 5000/box

Article Number	151-02570
Type	MSC901
Color	Metal (ML)
Quantity Per	box
Product Description	HellermannTyton's Metal Edge Clip provides an excellent alternative to managing wire and PV cables where plastic fasteners are not the preferred method. Designed for effortless insertion, the Metal Edge Clip has a high extraction force that tolerates extreme environments and provides assurance that the cables are secure on a panel. The Metal Edge Clip is simple to install and can easily be removed with a flathead screwdriver.
Short Description	Low Profile 90° Metal Edge Clip, 0.76–1.24mm Panel Thickness, 4–7.4mm Cable Range, SS304, 5000/box

Global Part Name	MSC901-SS304-ML
------------------	-----------------

Length L (Imperial)	0.73
---------------------	------

Length L (Metric)	18.44
-------------------	-------

Width W (Imperial)	0.460
--------------------	-------

Width W (Metric)	11.57
------------------	-------

Bundle Diameter Min (Imperial)	0.16
--------------------------------	------

Bundle Diameter Min (Metric)	4.1
------------------------------	-----

Bundle Diameter Max (Imperial)	0.29
--------------------------------	------

Bundle Diameter Max (Metric)	7.39
------------------------------	------

Depth D (Imperial)	0.560
--------------------	-------

Depth D (Metric)	14.224
------------------	--------

Panel Thickness Min (Imperial)	0.03
--------------------------------	------

Panel Thickness Max (Imperial)	0.05
--------------------------------	------

Panel Thickness Min (Metric)	0.76
------------------------------	------

Panel Thickness Max (Metric)	1.24
------------------------------	------

Material	Stainless Steel (SS304)
Material Shortcut	SS304
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
UL Listed (US and Canada)	Yes
UL Recognized (US and Canada)	Yes
UL Listed (US)	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	7326908695

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)